

CompactLogix™ 5370 L3 Programmable Automation Controllers



1769-L30ER, -L30ERM, -L30ER-NSE, -L33ER, -L33ERM, -L36ERM

Features and Benefits

The CompactLogix 5370 L3 controllers deliver scalable, affordable control ideal for applications from small stand-alone equipment to high performance indexing tables, process skids, case packers and erectors, and packaging.

Machine builders and end users can take advantage of the cost-saving features of these controllers:

- Support for Integrated Motion on EtherNet/IP
- Support for Device Level Ring (DLR) network topologies
- Built-in energy storage eliminates the need for lithium batteries
- Support reuse of existing 1769 I/O
- Removable 1GB secure digital (SD) card improves data integrity
- Flexible memory options up to 3MB
- Added features for hazardous environments (NSE version)
- Support for Kinematics eliminates the need for additional robot controllers and software
- Open socket capability allows support for Modbus TCP as well as devices such as printers, barcode readers and servers

Reduce cost and time to market with CompactLogix 5370 L3 Programmable Automation Controllers.



Expanding on the scalability of the Logix family of controllers, the CompactLogix 5370 L3 programmable automation controllers (PAC) are designed to meet the growing need for a higher performance controller in a compact and affordable package.

As part of the Integrated Architecture system, the CompactLogix 5370 L3 controllers use the same programming software, network protocol, and information capabilities as all Logix controllers, providing a common development environment for all control disciplines.

Integrated Motion on EtherNet/IP

The CompactLogix 5370 L3 controller provides a strong motion solution for customers looking for performance and cost competitiveness.

- Supports up to 16 axes of integrated motion
- Together with the Kinetix 350, offers cost-effective, scalable motion solution

Network Capabilities

With dual Ethernet ports and an integrated Ethernet switch, these controllers now support Device Level Ring (DLR) network topologies, simplifying integration of components in your control system and reducing system cost:

- Provides resiliency from loss of one network connection
- Allows replacement of devices one at a time without stopping production
- Reduces the number of Ethernet switches in the control system

Features for Hazardous Environments

The No Stored Energy (NSE) version of the CompactLogix 5370 L3 offers additional features for hazardous environments found in industries such as mining and oil and gas.

- Allows safe transport of controller in and out of mining areas
- Powered down controller has less than 200uJ of residual energy stored in each component
- No consequences of arc or spark to cause an explosion in gaseous environment

LISTEN.
THINK.
SOLVE.

CompactLogix 5370 L3 Controller Product Specifications

| | 1769-L30ER | 1769-L30ERM | 1769-L30ER-NSE | 1769-L33ER | 1769-L33ERM | 1769-L36ERM |
|--|---|--------------------------------------|----------------|------------|--------------------------------------|---------------------------------------|
| User memory | 1 MB | 1 MB | 1 MB | 2 MB | 2 MB | 3 MB |
| Controller tasks | 32 | 32 | 32 | 32 | 32 | 32 |
| Programs per task | 100 | 100 | 100 | 100 | 100 | 100 |
| Integrated Motion | -- | 4 axis CIP motion position loop axis | -- | -- | 8 axis CIP motion position loop axis | 16 axis CIP motion position loop axis |
| Package Size | 55mm wide x 118mm high x 105mm deep | | | | | |
| Certifications | cULH (Class I Division 2), KCC / UL (UL 508), ULH (Class I & II, Division 2 and Class III, Divisions 1 & 2) / ATEX, CE, C-Tick, GOST-R and Marine | | | | | |
| Local Expansion Modules | 8 | 8 | 8 | 16 | 16 | 30 |
| Local Expansion I/O Points (Max) | 256 | 256 | 256 | 512 | 512 | 960 |
| Communication Module Additions | DeviceNet with 1769-SDN or 3rd party | | | | | |
| Flash Memory Card | Industrially rated and certified Secure Digital (SD) memory card (1 and 2 GB options); all controllers shipped with 1 GB card | | | | | |
| Servo Drives (Position Loop CIP) | -- | 4 | -- | -- | 8 | 16 |
| Ethernet I/O IP nodes | 16 | 16 | 16 | 32 | 32 | 48 |
| Virtual axes | 100 | 100 | 100 | 100 | 100 | 100 |
| Feedback only, torque, velocity, Vhz (max CIP motion drives) | -- | 16 | -- | -- | 32 | 48 |
| Axes/ms | -- | 2 | -- | -- | 2 | 2 |
| Kinematics support | -- | yes | -- | -- | yes | yes |
| Software / Firmware | RSLogix 5000 V20 and RSLinx Classic V2.59 Firmware v20.1x or later | | | | | |

CompactLogix, Integrated Architecture, Kinetix, RSLogix, Integrated Motion on EtherNet/IP are trademarks of Rockwell Automation, inc. Trademarks not belonging to Rockwell Automation are property of their respective companies.

www.rockwellautomation.com

Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846