

GP4000 H SERIES



Enhanced Safety

Emergency Switch Switches are available in red, yellow or gray.







3-Position Enable Switch

A forced contact opening function is also equipped.



Key Switch

It allows you to move GP4000H without triggering the emergency stop.

Extremely Light



Clear Visibility



Excellent visibility with high definition and wide viewing angles..

TFT LCD:65,536-colors

Smart features in your hand

■ Simple replacement from GP3000H series



Compatible Accessories



Support for Monochrome Display



Resolution Converter

Specifications

	Product Name	GP-4311HT	
		Total Control	
	Model	PFXGP4311HTAD*	
	Display Type	TFT Color LCD	
	Display Size	5.7"	
	Display Colors	65,536 Colors (No blink) 16,384 Colorts (Blink)	
	Resolution	640 x 480 Pixels (VGA)	
Α	oplication Memory	32MB	
	Data Backup	SRAM 320KB	
	Input Voltage	24 Vdc	
	Serial	RS-232C/422/485	
	Ethernet	10BASE-T/100BASE-TX	
	Memory	SD Card	
	USB	Type A, mini-B	
Interface	External Output	DOUT x 2, Operation x 1, Buzzer x 1	
Inte	Function Switch	11 Switches (plus 1 Operation Switch)	
	Emergency Switch	Push-lock Switch	
	3-Position Enable Switch	Rear Panel S vitch 3-Position Ou put	
	Key Switch	Only support key switch models	

Options

Product Nan	ne	Model	Description
Hard-type Direct-connect Cable	10m	GP3000H-CBLH-10M	Heavy-duly type interface cable for communication between this product and attack arral equipment.
Soft-type Direct-Connect Cable	3m 5m 10m	GP3000H-CBLS-3M GP3000H-CBLS-5M GP3000H-CBLS-10N	Stal daid type interface cable for communication between this product and external equipment.
Hard-type Direct Connect Cable (with connecter)		GP3000H-CBLHD-17M	Heavy-duty type cable between Conversion Adapter and this prodct.
Soft-type Direct Connect Cable (with connecter)	3m 5m 10m	GP3000H-CBLSD-3M GP30C0H-CBLSD-5M GP30CH-CBLSD-10M	Standard type cable between Converstion Adapter and this product.
Conversion Adapter	<u>Q</u>	AGP3000H-ADPCOM-01	Conversion Adapter for interfacing with a Cable Connector and External Output 1/F output the following connectors; Serial: D-Sub 9 pin (plug) Ethernet: Modular Jack (RJ-45) Others: Terminal Block

■Model Number

Model	Description
PFXGP4311HTAD	Without any stop swith and key switch
PFXGP4311HTADER	With emergency stop switch (red), without key switch
PFXGP4311HTADERK	With emergency stop switch (red) and key switch
PFXGP4311HTADEYK	With stop switch (yellow) and key switch
PFXGP4311HTADEGK	With stop switch (gray) and key switch

Please check our website for more details.

A WARNING

HAZARD OF OPERATOR INJURY, OR UNINTENDED EQUIPMENT DAMAGE

Before operating any of these products, be sure to read all related manuals thoroughly, Failure to follow these instructions can result in death, serious injury or equipment damage.

- For printing purposes, the colors in this catalog may differ from those of the actual unit.
- All product names used in this catalog are the registered trademarks or trademarks of their respective companies.
- Actual user screens may differ from the screens shown here.

 Electric equipment should be installed, operated, serviced, and maintained only by qualified personnel. No responsibility is assumed by Digital for any consequences arising out of the use of this material.



Visit our website for more information.

www.proface.com

Global Headquarters Digital Electronics Corporation
[JAPAN] Tel: +81-(0)6-6208-3133

[AUSTRALIA] Tel: +61 (0)3 9550 7396 [CHINA] Tel: +86-(0)21-6361-5175 [FRANCE] Tel: +33 (0)1 60 21 22 91 [ITALY] Tel: +39 0362 59 96 1 [SINGAPORE] Tel: +65-6832-5533 [SWITZERLAND] Tel: +41 (0)43 343 7272

North/South American Headquarters Pro-face America, Inc. [U.S.A.] Tel: +1-734-477-0600

[AUSTRIA] Tel: +43 732 6933-0 [DENMARK] Tel: +45 70 22 01 22 [GERMANY] Tel: +49 (0)212 258 260 [THE NETHERLANDS] Tel: +31 23 55 44 094 [SOUTH KOREA] Tel: +82-(0)2-2630-9850 [TAIWAN] Tel: +886-(0)2-2657-1121

European Headquarters Pro-face Europe B.V. [THE NETHERLANDS] Tel: +31 (0)23 55 44 099

[BELGIUM] Tel: +32 2 373 77 11 [ENGLAND] Tel: +44 (0) 2476 847655 [INDIA] Tel: +91 80 4333 3540 [POLAND] Tel: +48 22 511 83 28 [SPAIN] Tel: +34 (0)93 846 07 45 [THAILAND] Tel: +66-(0)2-617-5678