



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL310	IC694MDL330	IC694MDL340	IC694MDL390
Product Name	PACSystems RX3i AC Voltage Output Module, 120 VAC, 0.5A, 12 Point Output	PACSystems RX3i AC Voltage Output Module, 120/240 VAC, 1A, 8 Point Output	PACSystems RX3i AC Voltage Output Module, 120 VAC, 0.5A, 16 Point Output	PACSystems RX3i AC Voltage Output Module, 120/240 VAC Isolated, 2A, 5 Point Output
Lifecycle Status	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Output Voltage Range	85-132 VAC	85-264 VAC	85-132 VAC	85-264 VAC
Number of Points	12	8	16	5
Isolation	N/A	N/A	N/A	Yes
Diagnostics	N/A	N/A	N/A	N/A
Load Current per Point	0.5 A	1 A	0.5 A	2 A
Response Time (ms)	1 on 1/2 cy off	1 on 1/2 cy off	1 on 1/2 cy off	1 on 1/2 cy off
Output Type	Triac	Triac	Triac	Triac
Polarity	N/A	N/A	N/A	N/A
Points per Common	6	4	4	1
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	210 mA @ 5 VDC	160 mA @ 5 VDC	315 mA @ 5 VDC	110 mA @ 5 VDC



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL350	IC694MDL732	IC694MDL734	IC694MDL740
Product Name	PACSystems RX3i AC Voltage Output Module, 120/240 VAC Isolated, 2A, 16 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic, 0.5A, 8 Point Output	PACSystems RX3i DC Voltage Output Module, 125 VDC Pos/Neg Logic, 6 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic, 0.5A, 16 Point Output
Lifecycle Status	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Output Voltage Range	74-264 VAC	12-24 VDC	11-150 VDC	12-24 VDC
Number of Points	16	8	6	16
Isolation	Yes	N/A	N/A	N/A
Diagnostics	N/A	N/A	N/A	N/A
Load Current per Point	Per Point 2A max. @ 30°C & 1A max. @ 60°C (Linear derating)	0.5 A	1 A	0.5 A
Response Time (ms)	1 on/1/2 cy off	2 on/2 off	7 on/5 off	2 on/2 off
Output Type	Triac	Transistor	Transistor	Transistor
Polarity	N/A	Positive	Positive/Negative	Positive
Points per Common	1	8	1	8
Connector Type	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	110 mA @ 5 VDC	50 mA @ 5 VDC	90 mA @ 5 VDC	110 mA @ 5 VDC



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL741	IC694MDL742	IC694MDL752	IC694MDL753
Product Name	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Negative Logic, 0.5A, 16 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic ESCP, 1A, 16 Point Output	PACSystems RX3i DC Voltage Output Module, 5/24 VDC (TTL) Negative Logic, 0.5A, 32 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic, 0.5A, 32 Point Output
Lifecycle Status	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Output Voltage Range	12-24 VDC	12-24 VDC	5, 12-24 VDC	12-24 VDC
Number of Points	16	16	32	32
Isolation	N/A	N/A	N/A	N/A
Diagnostics	N/A	N/A	N/A	N/A
Load Current per Point	0.5 A	1 A	0.5 A	0.5 A
Response Time (ms)	2 on/2 off	2 on/2 off	0.5 on/0.5 off	0.5 on/0.5 off
Output Type	Transistor	Transistor	Transistor	Transistor
Polarity	Negative	Positive	Negative	Positive
Points per Common	8	8	8	8
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Fujitsu Connector	Fujitsu Connector
Internal Power Used	110 mA @ 5 VDC	130 mA @ 5 VDC	260 mA @ 5 VDC	260 mA @ 5 VDC



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL758	IC694MDL754	IC695MDL765	IC694MDL930
Product Name	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic with ESCP (Self Healing) per group, 0.5 A, 32 Point Output (Two groups of 16)	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic with ESCP (Self Healing), 0.75 A, 32 Point Output	RX3i DC Voltage Output Module, 24/125 volt DC 2 A Smart Digital Output module, 16 Point Output	PACSystems RX3i AC/DC Voltage Output Module, Relay, N.O., 4 A Isolated, 8 Point Output
Lifecycle Status	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Output Voltage Range	12-24 VDC	12-24 VDC	18 to 30 VDC 105 to 132 VDC	0 to 125 VDC, 5/24/125 VDC nominal 0 to 265 VAC (47 to 63 Hz), 120/240 VAC nominal
Number of Points	32	32	16	8
Isolation	N/A	N/A	N/A	Yes
Diagnostics	Electronic Short Circuit Detection Per 16 points	Short Circuit Detection	<ul style="list-style-type: none"> • Output Pulse Test • Over temperature • Failed Switch Detection • Overload Detection and Shutdown • No-load Detection 	N/A
Load Current per Point	0.50 A	0.75 A	2 A	2 A
Response Time (ms)	0.5 on/0.5 off	0.5 on/0.5 off	1 msec maximum	15 on/15 off
Output Type	Transistor	Transistor	Transistor	Relay
Polarity	Positive	Positive	Positive	N/A
Points per Common	16	16	16	1
Connector Type	IC694TBBx32 or IC694TBSx32. Sold Separately.	IC694TBBx32 or IC694TBSx32. Sold Separately.	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.
Internal Power Used	250 mA @ 5 VDC	300 mA @ 5 VDC	540 mA @ 5.1 VDC; 152 mA @ 3.3 VDC	6 mA @ 5 VDC; 70 mA @ 24 VDC Relay



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL916	IC694MDL931	IC694MDL940	HE693RLY100	HE693RLY110
Product Name	PACSystems RX3i AC/DC Voltage Output Module, Relay, N.O., 4 A Isolated, 16 Point Output	PACSystems RX3i AC/DC Voltage Output Module, Relay, N.C. and Form C, 8 A Isolated, 8 Point Output	PACSystems RX3i AC/DC Voltage Output Module, Relay, N.O., 2 A, 16 Point Output	DC/AC Voltage Relay Output Module High Current	DC/AC Voltage Relay Output Module High Current (fused)
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1	1
Output Voltage Range	5 to 125 VDC 5/24/125 VDC nominal 5 to 250 VAC (47 to 63 Hz), 120/240 VAC nominal	0 to 125 VDC, 5/24/125 VDC nominal 0 to 265 VAC (47 to 63 Hz), 120/240 VAC nominal	0 to 125 VDC, 5/24/125 VDC nominal 0 to 265 VAC (47 to 63 Hz), 120/240 VAC nominal	12-120 VAC, 12-30 VDC	12-120 VAC, 12-30 VDC
Number of Points	16	8	16	8	8
Isolation	Yes	Yes	N/A	N/A	Yes
	N/A	N/A	N/A	N/A	N/A
Diagnostics					
Load Current per Point	4 A	8 A	2 A	8 A	8 A
Response Time (ms)	10ms maximum (At nominal voltage excluding contact bounce)	15 on/15 off	15 on/15 off	11 on/11 off	11 on/11 off
Output Type	Relay	Relay	Relay	Relay	Relay
Polarity	N/A	N/A	N/A	N/A	N/A
Points per Common	1	1	4	N/A	1
Connector Type	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	300 mA @ 5 VDC from backplane maximum (all outputs ON)	6 mA @ 5 VDC; 110 mA @ 24 VDC Relay	7 mA @ 5 VDC; 135 mA @ 24 VDC Relay	180 mA @ 5 VDC; 200 mA @ 24 VDC Relay	180 mA @ 5 VDC; 200 mA @ 24 VDC Relay



Analog I/O Modules (Output)

GE offers easy-to-use analog modules for control processes such as flow, temperature and pressure.

	IC694ALG392	IC695ALG704
Product Name	PACSystems RX3i Analog Output, Current/Voltage, 8 Channel	PACSystems RX3i Analog Output, Current/Voltage, 4 Channel
Lifecycle Status	Active	Active
Module Type	Analog Output	Analog Output
Backplane Support	No Backplane Restrictions	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1
Diagnostics	N/A	High and Low Alarm, Ramp Rate Control Clamping, Overrange and Underrange
Protection	Reverse polarity and undervoltage on external power supply	N/A
Range	0 V to +10 V, -10 V to +10 V, 0-20 mA, 4-20 mA	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V
HART Support	N/A	N/A
Number of Channels	8	4
Channel-to-Channel Isolation	N/A	N/A
Update Rate	8 ms all channels	8 ms all channels
Resolution	16 bit; 0.312 mV/bit	±10 V: 15.9 bits; 0 to 10 V: 14.9 bits; 0 to 20 mA: 15.9 bits; 4 to 20 mA: 15.6 bits
Accuracy	0-20 mA, 4-20 mA ±0.1% at 25°C (77°F); 0-10 V, -10F + 10 V ±0.25 at 25°C (77°F)	Accurate to within 0.15% of full scale at 25°C. Accurate to within 0.30% of full scale at 60°C
Maximum Output Load	5 mA (2 K ohms)	Current -850ohm max @ Vuser = 20 V; Voltage -2k ohm max load (minimum resistance)
Output Load Capacitance	2000 pF, Inductance 1H	Current: 10uH max.; Voltage: 1uF max.
External Power Requirement	N/A	Voltage Range: 19.2 V to 30 V Current required: 160 mA
Connector Type	Terminal Block (20 screws), included with module.	IC694TBB032 or IC694TBS032. Sold Separately.
Internal Power Used	110 mA @ 5 VDC; 315 mA -User Supplied 24 VDC	375 mA @ 3.3 V (internal) 160 mA @ 24 V (external)



Analog I/O Modules (Output)

GE offers easy-to-use analog modules for control processes such as flow, temperature and pressure.

	IC695ALG708	IC695ALG728
Product Name	PACSystems RX3i Analog Output, Current/Voltage, 8 Channel	PACSystems RX3i Analog Output with HART Communications, Current/Voltage, 8 Channel
Lifecycle Status	Active	Active
Module Type	Analog Output	Analog Output with HART Communications
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1
Diagnostics	High and Low Alarm, Ramp Rate Control Clamping, Overrange and Underrange	High and Low Alarm, Ramp Rate Control, Clamping, Overrange and Underrange
Protection	N/A	N/A
Range	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V
HART Support	N/A	-Get HART Device Information (Function 1) Simplified HART Pass-Thru Command (Function 2) -Enterprise HART Pass-Thru Command (Function 3)
Number of Channels	8	8
Channel-to-Channel Isolation	N/A	N/A
Update Rate	8 ms all channels	8 ms all channels and HART enabled channels could add 6 to 8 seconds.
Resolution	10 V: 15.9 bits; 0 to 10 V: 14.9 bits; 0 to 20 mA: 15.9 bits; 4 to 20 mA: 15.6 bits	±10 V: 15.9 bits; 0 to 10 V: 14.9 bits; 0 to 20 mA: 15.9 bits; 4 to 20 mA: 15.6 bits
Accuracy	Accurate to within 0.15% of full scale at 25°C. Accurate to within 0.30% of full scale at 60°C	Accurate to within 0.15% of full scale at 25°C. Accurate to within 0.30% of full scale at 60°C
Maximum Output Load	Current -850ohm max @ Vuser = 20 V; Voltage -2k ohm max load (minimum resistance)	Current -850ohm max @ Vuser = 20 V; Voltage -2k ohm max load (minimum resistance)
Output Load Capacitance	Current: 10uH max.; Voltage: 1uF max.	Current: 10uH max.; Voltage: 1uF max.
External Power Requirement	Voltage Range: 19.2 V to 30 V Current required: 315 mA	Voltage Range: 19.2 V to 30 V Current required: 315 mA
Connector Type	IC694TBB032 or IC694TBS032. Sold Separately	IC694TBB032 or IC694TBS032. Sold Separately.
Internal Power Used	375 mA @ 3.3 V (internal) 315 mA @ 24 V (external)	375 mA @ 3.3 V (internal) 315 mA @ 24 V (external)



Analog I/O Modules (Output)

GE offers easy-to-use analog modules for control processes such as flow, temperature and pressure.

	IC695ALG808	IC694ALG390	IC694ALG391
Product Name	PACSystems RX3i Isolated Analog Output, Current/Voltage, 8 Isolated Channels	PACSystems RX3i Analog Output, Voltage, 2 Channel	PACSystems RX3i Analog Output, Current, 2 Channel
Lifecycle Status	Active	Active	Active
Module Type	Analog Output with Channel to Channel Isolation	Analog Output	Analog Output
Backplane Support	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1
Diagnostics	High and Low Alarm, Ramp Rate Control, Clamping, Overrange and Underrange	N/A	N/A
Protection	N/A	N/A	N/A
Range	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V	-10 V to +10 V, 4-20 mA	1-5 V and 0-5 V, 0-20 mA, 4-20 mA
HART Support	N/A	N/A	N/A
Number of Channels	8	2	2
Channel-to-Channel Isolation	Yes (250 VAC continuous, 1500 VAC for 1 minute per channel)	N/A	N/A
Update Rate	8 ms all channels (1 msec per channel)	5 ms all channels	5 ms all channels
Resolution	±10 V @ 15.9 bits minimum 0 to 10 V @ 14.9 bits minimum 0 to 20 mA @ 15.9 bits minimum 4 to 20 mA @ 15.6 bits minimum	12 bit; 2.5 mV/bit	12 bit; 0-20 mA, 5µA/bit
Accuracy	Accurate to within ±0.1% of span at 25°C, ± 0.25% of span over operating temperature range	±5 mV at 25°C (77°F)	0-20 mA, ±8 µA at 25°C (77°F); 0-20 mA, 4-20 mA ±0.1% at 25°C (77°F)
Maximum Output Load	Current: 1350 ohm maximum resistance, 10uH max inductance Voltage: 2k Ohm minimum resistance, 1uF max capacitance	5 mA (2 K ohms)	5 mA (2 K ohms)
Output Load Capacitance	Current: 10uH max.; Voltage: 1uF max.	2000 pF	2000 pF, Inductance 1H
External Power Requirement	500 mA @ 24 VDC	N/A	N/A
Connector Type	IC694TBBx32 or IC694TBSx32 Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	450 mA @ 3.3 V Maximum, all channels on	32 mA @ 5 VDC; 120 mA @ 24 VDC Isolated	30 mA @ 5 VDC; 215 mA 24 VDC Isolated



Analog I/O Modules (Output)

GE offers easy-to-use analog modules for control processes such as flow, temperature and pressure.

	HE693DAC410	HE693DAC420
Product Name	Isolated Analog Output Module, Voltage	Isolated Analog Output Module, Current
Lifecycle Status	Active	Active
Module Type	Analog Output	Analog Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Diagnostics	N/A	N/A
Protection	N/A	N/A
Range	±10 V	4-20 mA or 0-20 mA
HART Support	N/A	N/A
Number of Channels	4	4
Channel-to-Channel Isolation	1500 VAC (RMS), ±2000 VDC	1500 VAC (RMS), ±2000 VDC
Update Rate	N/A	N/A
Resolution	1.2 5 mV	2.0 µA (4-20 mA); 2.5 µA (±20 mA)
Accuracy	N/A	N/A
Maximum Output Load	N/A	N/A
Output Load Capacitance	N/A	N/A
External Power Requirement	N/A	2-32 VDC
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	500 mA @ 5 VDC; 150 mA @ 24 VDC Relay	150 mA @ 5 VDC; 110 mA @ 24 VDC Relay



Analog Mixed I/O Modules (Input and Output)

The analog mixed modules (four in and two out) are available with or without advanced diagnostics. The advanced diagnostics includes alarms, open wire, rate of change, over range and under range. Additional features include 16 bit resolution, analog output clamp limits and output ramp mode option.

	IC694ALG542	IC694ALG442
Lifecycle Status	Active	Active
Module Type	Analog Combination 4 In and 2 Out with Advanced Diagnostics, Output Clamp and Ramp Control	Analog Combination 4 In and 2 Out
Backplane Support	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Range	0 V to +10 V, -10 V to +10 V, 0-20 mA, 4-20 mA per Channel	0 V to +10 V, -10 V to +10 V, 0-20 mA, 4-20 mA per Channel
Channel-to-Channel Isolation	N/A	N/A
Number of Channels	4 in/2 out	4 in/2 out
Update Rate	2ms all channels	2ms all channels
Resolution	(Input)16 bit; 0 V to 10 V, 0.3125 mV/bit; -10 V to +10 V, 0.3125 mV/bit; 0-20 mA, 0.625 μ A 4-20 mA 0.5 μ A/bit (Output) 16 bit; 0 to 20 mA: 0.625 μ A; 4 to 20 mA: 0.5 μ A; -10 V to +10 V: 0.3125 mV; 0 to +10 V: 0.3125 mV	(Input)12 bit; 0 V to 10 V, 2.5 mV/bit; -10 V to +10 V, 5 mV/bit; 0-20 mA,4-20 mA 5 μ A/bit (Output) 16 bit; 0.312 mV/bit; 4-20 mA 0.5 μ A/bit; 0-20 mA 0.625 μ A/bit
Accuracy	Current Input 0 to 20 mA \pm 0.25% of full scale @ 25°C (77°F); \pm 0.5% of full scale over specified operating temperature range Current Input 4 to 20 mA \pm 0.25% of full scale @ 25°C (77°F); \pm 0.5% of full scale over specified operating temperature range 4 to 20 mA Enhanced Mode \pm 0.25% of full scale @ 25°C (77°F); \pm 0.5% of full scale over specified operating temperature range Current Output \pm 0.1% of full scale @ 25°C (77°F), typical \pm 0.25% of full scale @ 25°C (77°F), maximum \pm 0.5% of full scale over operating temperature range (maximum) Voltage Output \pm 0.25% of full scale @ 25°C (77°F), typical \pm 0.5% of full scale @ 25°C (77°F), maximum \pm 1.0% of full scale over operating temperature range (maximum)	(Input) 0.25 μ A; at 25°C (77°F) (Output) 0-20 mA, 4-20 mA \pm 0.1% at 25°C (77°F) (77°F)
Input Impedence	Current mode - 250 ohms Voltage mode - 800 K ohms	Current mode - 250 ohms Voltage mode - 800 K ohms"
Input Filter Response	Current mode - 55 Hz Voltage mode - 55 Hz	Current mode - 38 Hz Voltage mode - 38 Hz
Maximum Output Load	Voltage: 5 mA (2 K ohms) Current Inductance:1 H (maximum)	Voltage: 5 mA (2 K ohms) Current Inductance:1 H (maximum) "
Output Load Capacitance	Voltage:1 μ F (maximum) Current: 2000 pF (maximum)	Voltage:1 μ F (maximum) Current: 2000 pF (maximum)"
Diagnostics	Under Range/Over Range, Open Wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	N/A
Internal Power Used	95 mA \pm 4; 5 VDC; 150 mA external 24 VDC Isolated	95 mA \pm 4; 5 VDC; 150 mA external 24 VDC Isolated
External Power Requirement	24VDC: Current: 5 μ A/V (typical), 10 μ A/V (maximum) Voltage: 25 mV/V (typical), 50 mV/V (maximum)	24VDC: Current: 5 μ A/V (typical), 10 μ A/V (maximum) Voltage: 25 mV/V (typical), 50 mV/V (maximum)
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.



Millivolt I/O Modules

The Millivolt Input Modules allow Millivolt level signals, such as bridged strain gages (load cells) to be directly connected to the PLC without external signal processing (transducers, transmitters, etc.) All analog and digital processing of the signal is performed on the module.

	IC695ALG600 Millivolt	IC695ALG306 Millivolt
Product Name	Universal Analog and configurable for Current, Voltage, RTD, Thermocouple and Resistive. High Density (8 Channel) Requires Cold Junction Compensation; are available for Thermocouple configurations (IC695ACC600 contains 2 CJs)	Isolated Thermocouple Input module provides six isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.
Lifecycle Status	Active	Active
Module Type	Millivolt Input	Strain Gage Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1
Range	$\pm 150\text{mV}$ or $\pm 50\text{mV}$	$\pm 150\text{mV}$ or $\pm 50\text{mV}$
Diagnostics	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low
Channel-to-Channel Isolation	Two Groups of Four	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second
Number of Channels	8	6
Notch Filter	Yes	From 2.3 Hz to 28 Hz per channel
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format)	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format)
Accuracy	Calibrated Accuracy at 25°C. Better than 0.1% of range. Accuracy depends on A/D filter, data format, input noise, and ambient temperature.	$\pm 0.1\%$ of voltage span at 25°C. $\pm 0.25\%$ of span over temperature range.
Input Impedance	>1M ohm	Voltage: $\geq 500\text{k ohm}$
I/O Required	N/A	N/A
A/D Conversion Type	Sigma Delta	Sigma Delta
A/D Conversion Time	(Assumes 2 ADC's running in parallel, no CJC or lead resistance) 10ms per Channel 4 Channels = 40ms (1KHz filter) 127ms per Channel 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	15 msec @ 28 Hz to 120 msec @ 2.3 Hz
Strain Gages Supported	Yes	Yes
Maximum Normal Voltage Input	N/A	N/A
Maximum Voltage Input	$\pm 14.5\text{ VDC}$ continuous	N/A
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.
Internal Power Used	400 mA @ 5 V; 350 mA @ 3.3 V	150 mA @ 5V; 400 mA @ 3.3V



Millivolt I/O Modules

The Millivolt Input Modules allow Millivolt level signals, such as bridged strain gages (load cells) to be directly connected to the PLC without external signal processing (transducers, transmitters, etc.) All analog and digital processing of the signal is performed on the module.

	IC695ALG312 Millivolt	HE693ADC409
Product Name	Isolated Thermocouple Input module provides twelve isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.	Analog I/O Module, Millivolt Input
Lifecycle Status	Active	Active
Module Type	Strain Gage Input	Millivolt Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Range	$\pm 150\text{mV}$ or $\pm 50\text{mV}$	$\pm 25\text{ mV}$, $\pm 50\text{ mV}$ and $\pm 100\text{ mV}$
Diagnostics	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	N/A
Channel-to-Channel Isolation	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second	N/A
Number of Channels	12	4
Notch Filter	From 2.3 Hz to 28 Hz per channel	N/A
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	3 μV , 6 μV , 9 μV (respectively)
Accuracy	$\pm 0.1\%$ of voltage span at 25°C $\pm 0.25\%$ of span over temperature range.	$\pm 0.5\%$
Input Impedance	Voltage: $\geq 500\text{k ohm}$	$> 20\text{ Mohms}$
I/O Required	N/A	4% AI
A/D Conversion Type	Sigma Delta	Integrating
A/D Conversion Time	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	35 Channels/second
Strain Gages Supported	Yes	Bridged (load cells)
Maximum Normal Voltage Input	N/A	100 mV
Maximum Voltage Input	N/A	$\pm 35\text{ V}$
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	Terminal Block (20 screws), included with module.
Internal Power Used	300 mA @ 5 V; 400 mA @ 3.3 V	100 mA @ 5 VDC



RTD I/O Modules

The RTD Input Modules provide RTD inputs that allow the direct connection of 2 and 3-wire RTD temperature sensors without using external signal processing (transducers, transmitters, etc.). All analog and digital processing of the RTD signal is performed on the module.

	IC695ALG600 RTD	IC695ALG508 RTD	HE693RTD600
Product Name	Universal Analog and configurable for Current, Voltage, RTD, Thermocouple and Resistive. High Density (8 Channel) Requires Cold Junction Compensation; are available for Thermocouple configurations (IC695ACC600 contains 2 CJs)	Isolated RTD Input module (also supports Resistive) provides eight isolated differential Resistive or RTD input channels. Each channel can be individually configured for 2, 3, 4 wire RTD or Resistance.	RTD Input Module, Low Resolution
Lifecycle Status	Active	Active	Active
Module Type	RTD Input	RTD (and Resistive) Input Channel to Channel Isolation	RTD Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1
Number of Channels	8	8	6
RTD Types Supported	2 and 3 wire PT 385 / 3916, N 618 / 672, NiFe 518, CU 426	2, 3 and 4 wire 50, 100, 200, 500, and 1000 ohm Pt 385; 50, 100, 200, 500, and 1000 ohm Pt 391.6; 100, 200, 500, and 1000 ohm Ni 618; 120 ohm Ni 672; 604 ohm NiFe 518; 10, 50 and 100 ohm Cu 426	3-wire, Pt-100E, Pt-100C, Pt-100Z, Pt-1000, Cu-10, Cu-50, PT-100, Cu-53, Cu-100, Ni-120, TD5R, TD5R, Pt-90 (MIL-7990)
Diagnostics	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low	N/A
Channel-to-Channel Isolation	Two Groups of Four	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second	N/A
Notch Filter	Yes	N/A	N/A
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	0.5°C or 0.5°F
Accuracy	Calibrated Accuracy at 25°C. Better than 0.1% of range. Accuracy depends on A/D filter, data format, input noise, and ambient temperature.	Calibrated Accuracy at 25°C. Typical is ±0.5%	±0.5°C, typical
Input Impedance	>1M ohm	N/A	>1000 Megohms
I/O Required	N/A	N/A	6 %AI
Fault Protection	N/A	N/A	Zener Diode Clamp
Update Time	10ms per Channel; 4 Channels = 40ms (1KHz filter)127ms per Channel * 4 Channels = 508ms (8Hz filter)Channels that are disabled are not scanned, shortening scan time.	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	50 Channels/second
A/D Conversion Type	Sigma Delta	Sigma Delta	18 bit, integrating
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	Terminal Block (20 screws), included with module.
Internal Power Used	400 mA @ 5 V; 350 mA @ 3.3 V	150 mA @ 5 V; 300 mA @ 3.3 V	70 mA @ 5 VDC



RTD I/O Modules

The RTD Input Modules provide RTD inputs that allow the direct connection of 2 and 3-wire RTD temperature sensors without using external signal processing (transducers, transmitters, etc.). All analog and digital processing of the RTD signal is performed on the module.

	HE693RTD601	HE693RTD660
Product Name	RTD Input Module, High Resolution	RTD Input Module, Isolated
Lifecycle Status	Active	Active
Module Type	RTD Input	RTD Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Number of Channels	6	6
RTD Types Supported	3-wire, Pt-100E, Pt-100C, Pt-100Z, Pt-1000, Cu-10, Cu-50, PT-100, Cu-53, Cu-100, Ni-120, TD5R, TD5R, Pt-90 (MIL-7990)	3 wire, Pt-100E, Pt-100C, Ni-120, Cu-10, Pt-1000, TD5R Si
Diagnostics	N/A	N/A
Channel-to-Channel Isolation	N/A	5 VAC
Notch Filter	N/A	None
Resolution	0.125°C, 0.1°C, or 0.1°F	0.05°C, 0.05°F, 0.1°C, 0.1°F, 0.5°C or 0.5°F
Accuracy	±0.5°C, typical	±0.3°C
Input Impedance	>1000 Megohms	>1000 Megohms
I/O Required	6 %AI	6% AI, 6% AQ, 16% I
Fault Protection	Zener Diode Clamp	Suppression Diode
Update Time	50 Channels/second	50 Channels/second
A/D Conversion Type	18 bit, integrating	18 bit, integrating
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	70 mA @ 5 VDC	200 mA @ 5 VDC



Strain Gage I/O Modules

The Millivolt Input Modules allow Millivolt level signals, such as bridged strain gages (load cells) to be directly connected to the PLC without external signal processing (transducers, transmitters, etc.) All analog and digital processing of the signal is performed on the module.

	IC695ALG600 Strain Gage	IC695ALG306 Strain Gage	IC695ALG312 Strain Gage
Product Name	Universal Analog and configurable for Current, Voltage, RTD, Thermocouple and Resistive. High Density (8 Channel) Requires Cold Junction Compensation; are available for Thermocouple configurations (IC695ACC600 contains 2 CJs)	Isolated Thermocouple Input module provides six isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.	Isolated Thermocouple Input module provides twelve isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.
Lifecycle Status	Active	Active	Active
Module Type	Strain Gage Input	Strain Gage Input	Strain Gage Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1	1
Range	$\pm 150\text{mV}$ or $\pm 50\text{mV}$	$\pm 150\text{mV}$ or $\pm 50\text{mV}$	$\pm 150\text{mV}$ or $\pm 50\text{mV}$
Diagnostics	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low
Channel-to-Channel Isolation	Two Groups of Four	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second
Number of Channels	8	6	12
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format
Accuracy	Calibrated Accuracy at 25°C. Better than 0.1% of range. Accuracy depends on A/D filter, data format, input noise, and ambient temperature.	$\pm 0.1\%$ of voltage span at 25°C. $\pm 0.25\%$ of span over temperature range.	$\pm 0.1\%$ of voltage span at 25°C. $\pm 0.25\%$ of span over temperature range.
Input Impedance	>1M ohm	Voltage: $\geq 500\text{k ohm}$	Voltage: $\geq 500\text{k ohm}$
I/O Required	N/A	N/A	N/A
A/D Conversion Type	Sigma Delta	Sigma Delta	Sigma Delta
A/D Conversion Time	(Assumes 2 ADC's running in parallel, no CJC or lead resistance) 10ms per Channel 4 Channels = 40ms (1KHz filter) 127ms per Channel 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	15 msec @ 28 Hz to 120 msec @ 2.3 Hz
Strain Gages Supported	Yes	Yes	Yes
Maximum Normal Voltage Input	N/A	N/A	N/A
Maximum Voltage Input	± 14.5 VDC continuous	N/A	N/A
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.
Internal Power Used	400 mA @ 5 V; 350 mA @ 3.3 V	150 mA @ 5 V; 400 mA @ 3.3 V	300 mA @ 5 V; 400 mA @ 3.3 V



Strain Gage I/O Modules

The Millivolt Input Modules allow Millivolt level signals, such as bridged strain gages (load cells) to be directly connected to the PLC without external signal processing (transducers, transmitters, etc.) All analog and digital processing of the signal is performed on the module.

	IC695ALG412	HE693STG883	HE693STG884
Product Name	Isolated Thermocouple Input module provides twelve isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$. Offers a 10 dB improvement in noise rejection compared to ALG312 thermocouple inputs.	Analog I/O Module, Strain Gage	Analog I/O Module, Strain Gage
Lifecycle Status	Active	Active	Active
Module Type	Strain Gage Input	Strain Gage Input	Strain Gage Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1
Range	$\pm 50\text{mV}$	N/A	N/A
Diagnostics	Open wire, Short Circuit, Positive/Negative rate of Change, High, High-High, Low, Low-Low	N/A	N/A
Channel-to-Channel Isolation	Channel to Channel Isolation. 250VAC Continuous; 1500VAC 1 minute; 2550VDC 1 second	N/A	N/A
Number of Channels	12	8	8
Resolution	32-bit IEEE floating point or 16 bit integer (in 32 bit field) input data format	0.6 μV , 0.8 μV , 0.9 μV (respectively)	0.8 μV , 1.6 μV , 3.2 μV (respectively)
Accuracy	$\pm 0.1\%$ of voltage sp+GC+GB59GD1+GC59163an at 25 °C. $\pm 0.25\%$ of span over temperature range.	$\pm 0.3\%$	$\pm 0.3\%$
Input Impedance	Voltage: $\geq 500\text{k ohm}$	>1000 Mohms	>1000 Mohms
I/O Required	N/A	8% AI, 16% I, 8% AQ, 16% Q	8% AI, 16% I, 8% AQ, 16% Q
A/D Conversion Type	Sigma Delta	Integrating	Integrating
A/D Conversion Time	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	35 Channels/second	35 Channels/second
Strain Gages Supported	Yes	Bridged (load cells)	Bridged (load cells)
Maximum Normal Voltage Input		100 mV	100 mV
Maximum Voltage Input		± 35 V	± 35 V
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	425 mA @ 5 V; 400 mA @ 3.3 V	60 mA @ 5 VDC; 30 mA @ 24 VDC Relay	60 mA @ 5 VDC; 30 mA @ 24 VDC Relay



Temperature Control Modules

The Temperature Control Module (TCM), is a high performance control module providing eight channels of thermocouple input and eight channels of control output in a single RX3i module. Each channel can operate in closed or open loop mode relieving the PLC of providing the temperature control functions. The module also supports Autotuning.

	IC693TCM302	IC693TCM303
Product Name	PACSystems RX3i Temperature Control Module, (8) T/C, (1) RTD and (8) 24 VDC Output	PACSystems RX3i Temperature Control Module, Extended Range, (8) T/C, (1) RTD and (8) 24 VDC Output
Lifecycle Status	Mature	Mature
Module Type	Temperature Control	Temperature Control
Backplane Support	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Number of Channels	8 T/C In/ 8 DC Out	8 T/C In/ 8 DC Out
Range	J=0-600°C K=0-1050°C L=0-600°C	J=0-450°C K=0-600°C L=0-450°C
Output Voltage Range	18 to 30 volts DC	18 to 30 volts DC
Load Current per Point	100 mA maximum sourcing	100 mA maximum sourcing
Diagnostics	Open thermocouple and reverse connection detection capability Detection and indication of out-of-tolerance temperature readings	Open thermocouple and reverse connection detection capability Detection and indication of out-of-tolerance temperature readings
Connector Type	Two 20 pin connectors (screw type)	Two 20 pin connectors (screw type)
Internal Power Used	150 mA @ 5 VDC	150 mA @ 5 VDC



Thermocouple I/O Modules

The Thermocouple Input Modules allow thermocouple temperature sensors to be directly connected to the PLC with external signal processing (transducers, transmitters, etc.). The module performs all analog and digital processing of the thermocouple signal. The enhanced thermocouple input modules add isolation or high-resolution. On these modules, each channel can be configured for a specific type of sensor wire. An autodetect external AD592 cold junction compensation feature is also available.

	IC695ALG600 Thermocouple	IC695ALG306	IC695ALG312	IC695ALG412
Product Name	Universal Analog and configurable for Current, Voltage, RTD, Thermocouple and Resistive. High Density (8 Channel) Requires Cold Junction Compensation; are available for Thermocouple configurations (IC695ACC600 contains 2 CJs)	Isolated Thermocouple Input module provides six isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.	Isolated Thermocouple Input module provides twelve isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 150\text{mV}$ or $\pm 50\text{mV}$.	Isolated Thermocouple Input module provides twelve isolated differential thermocouple input channels. Each channel can be individually configured for inputs from: Thermocouple types: J, K, T, E, R, S, B, N, or C and Voltage: $\pm 50\text{mV}$. The ALG412 offers a 10dB improvement in noise rejection compared to the ALG312 thermocouple input module.
Lifecycle Status	Active	Active	Active	Active
Module Type	Thermocouple Input	Thermocouple Input	Thermocouple Input	Thermocouple Input
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1	1	1
Range	B, C, E, J, K, N, R, S, T	J, K, T, E, R, S, B, N, or C	J, K, T, E, R, S, B, N, or C	J, K, T, E, R, S, B, N, or C
Diagnostics	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low	Open wire, Short Circuit, Positive/Negative Rate of Change, High, High-High, Low, Low-Low
Number of Channels	8	6	12	12
Channel-to-Channel Isolation	Two Groups of Four	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second
Common Mode Rejection	120dB minimum @ 50/60 Hz with 8 Hz filter 110dB minimum @ 50/60 Hz with 12 Hz filter	2.3 Hz filter, 50/60Hz: 100 dB 4 Hz filter, 50Hz: 100 dB 4.7 Hz filter, 60Hz: 100 dB	2.3 Hz filter, 50/60Hz: 100 dB 4 Hz filter, 50Hz: 100 dB 4.7 Hz filter, 60Hz: 100 dB	All filters, 50/60 Hz: 110 dB
Channel to Channel Crosstalk		70 dB minimum	70 dB minimum	70 dB minimum
Notch Filter	Yes	From 2.3 Hz to 28 Hz per channel	From 2.3 Hz to 28 Hz per channel	From 2.3 Hz to 28 Hz per channel
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format
Accuracy	Calibrated Accuracy at 25°C. Better than 0.1% of range. Accuracy depends on A/D filter, data format, input noise, and ambient temperature.	$\pm 0.1\%$ of voltage span at 25°C. $\pm 0.25\%$ of span over temperature range.	$\pm 0.1\%$ of voltage span at 25°C $\pm 0.25\%$ of span over temperature range.	$\pm 0.1\%$ of voltage span at 25°C $\pm 0.25\%$ of span over temperature range.
Update Rate	10ms per Channel; 4 Channels = 40ms (1KHz filter) 127ms per Channel * 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	10ms per Channel; 4 Channels = 40ms (1KHz filter) 127ms per Channel * 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	10ms per Channel; 4 Channels = 40ms (1KHz filter) 127ms per Channel * 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	Configurable from 15 msec to 120 msec.
I/O Required	N/A	N/A	N/A	N/A
A/D Conversion Type	Sigma Delta	Sigma Delta	Sigma Delta	Sigma Delta
A/D Conversion Time	(Assumes 2 ADC's running in parallel, no CJC or lead resistance) 10ms per Channel 4 Channels = 40ms (1KHz filter) 127ms per Channel 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	15 msec @ 28 Hz to 120 msec @ 2.3 Hz	15 msec @ 28 Hz to 120 msec @ 2.3 Hz
Connector Type	IC694TB3x32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TB3x32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TB3x32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TB3x32, IC694TBSx32 or IC694TBC032. Sold Separately.
Internal Power Used	400 mA @ 5 V; 350 mA @ 3.3 V	225 mA @ 5V; 400 mA @ 3.3V	425mA @ 5V; 400 mA @ 3.3V	425mA @ 5V; 400 mA @ 3.3V



Thermocouple I/O Modules

The Thermocouple Input Modules allow thermocouple temperature sensors to be directly connected to the PLC with external signal processing (transducers, transmitters, etc.). The module performs all analog and digital processing of the thermocouple signal. The enhanced thermocouple input modules add isolation or high-resolution. On these modules, each channel can be configured for a specific type of sensor wire. An autodetect external AD592 cold junction compensation feature is also available.

	HE693THM166	HE693THM409	HE693THM449
	Analog I/O Thermocouple Input Module	Analog I/O Thermocouple Input Module	Analog I/O Thermocouple Input Module
Product Name			
Lifecycle Status	Active	Active	Active
Module Type	Thermocouple Input	Thermocouple Input	Thermocouple Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1
Range	J, K, N, T, E, R, S, B, C, X	J, K, N, T, E, R, S,	J, K, N, T, E, R, S,
Diagnostics	Yes	No	Yes
Number of Channels	16	4	4
Channel-to-Channel Isolation	N/A	N/A	N/A
Common Mode Rejection	N/A	N/A	N/A
Channel to Channel Crosstalk	N/A	N/A	N/A
Notch Filter	N/A	N/A	N/A
Resolution	0.5°C or 0.5°F	0.5°C or 0.5°F	0.5°C or 0.5°F
Accuracy	±0.5°C, typical (J, K, N, T)	±0.5°C, typical (J, K, N, T)	±0.5°C, typical (J, K, N, T)
Update Rate	N/A	N/A	N/A
I/O Required	16% AI, 16% I	4% AI	4% AI, 16% I
A/D Conversion Type	Integrating	Integrating	Integrating
	40 Channels/second	40 Channels/second	40 Channels/second
A/D Conversion Time			
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	80 mA @ 5 VDC; 30 mA @ 24 VDC Relay	80 mA @ 5 VDC; 60 mA @ 24 VDC Relay	80 mA @ 5 VDC; 60 mA @ 24 VDC Relay



Thermocouple I/O Modules

The Thermocouple Input Modules allow thermocouple temperature sensors to be directly connected to the PLC with external signal processing (transducers, transmitters, etc.). The module performs all analog and digital processing of the thermocouple signal. The enhanced thermocouple input modules add isolation or high-resolution. On these modules, each channel can be configured for a specific type of sensor wire. An autodetect external AD592 cold junction compensation feature is also available.

	HE693THM809	HE693THM884	HE693THM888	HE693THM889
	Analog I/O Thermocouple Input Module	Analog I/O Thermocouple Input Module (Enhanced)	Analog I/O Thermocouple Input Module (Enhanced)	Analog I/O Thermocouple Input Module
Product Name				
Lifecycle Status	Active	Active	Active	Active
Module Type	Thermocouple Input	Thermocouple Input	Thermocouple Input	Thermocouple Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Range	J, K, N, T, E, R, S	J, K, N, T, E, R, S, B, C	J, K, N, T, E, R, S, B, C	J, K, N, T, E, R, S
Diagnostics	No	Yes	Yes	Yes
Number of Channels	8	8	8	8
Channel-to-Channel Isolation	N/A	N/A	N/A	N/A
Common Mode Rejection	N/A	N/A	N/A	N/A
Channel to Channel Crosstalk	N/A	N/A	N/A	N/A
Notch Filter	N/A	None	60 Hz	N/A
Resolution	0.5°C or 0.5°F	N/A	N/A	0.5°C or 0.5°F
Accuracy	±0.5°C, typical (J,K,N,T)	N/A	N/A	±0.5°C, typical (J,K,N,T)
Update Rate	N/A	N/A	N/A	N/A
I/O Required	8% AI	8% AI, 8% AQ, 16% I	8% AI, 8% AQ, 16% I	8% AI, 16% I
A/D Conversion Type	Integrating	Integrating	Integrating	Integrating
	40 Channels/second	N/A	N/A	40 Channels/second
A/D Conversion Time				
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	80 mA @ 5 VDC; 60 mA @ 24 VDC Relay	100 mA @ 5 VDC; 60 mA @ 24 VDC Relay	100 mA @ 5 VDC; 60 mA @ 24 VDC Relay	80 mA @ 5 VDC; 60 mA @ 24 VDC Relay



Resistive I/O Module

The Resistive module allows the user to easily connect to resistive loads without the need of external devices.

	IC695ALG600 Resistive	IC695ALG508 Resistive
Product Name	Universal Analog and configurable for Current, Voltage, RTD, Thermocouple and Resistive. High Density (8 Channel) Requires Cold Junction Compensation; are available for Thermocouple configurations (IC695ACC600 contains 2 CJs)	Isolated Resistive Input module (also supports RTD) provides eight isolated differential Resistive or RTD input channels. Each channel can be individually configured for 2, 3, 4 wire RTD or Resistance.
Lifecycle Status	Active	Active
Module Type	Resistive Input	Resistive (and RTD) Input Channel to Channel Isolation
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1
Range	0 to 250 / 500 / 1000 / 2000 / 3000 / 4000 Ohms	250 / 500 / 1000 / 2000 / 3000 / 4000 Ohms
Diagnostics	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low	Open wire, short circuit, positive/negative rate of change, High, High-High, Low, Low-Low
Number of Channels	8	8
Channel-to-Channel Isolation	Two Groups of Four	250 VAC Continuous 1500 VAC 1 minute 2550 VDC 1 second
Notch Filter	Yes	N/A
Resolution	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format	32-bit IEEE floating point or 16-bit integer (in 32-bit field) input data format
Accuracy	Calibrated Accuracy at 25°C. Better than 0.1% of range. Accuracy depends on A/D filter, data format, input noise, and ambient temperature.	Calibrated Accuracy at 25°C. Typical is ± 0.5%
Input Impedance	>1M ohm	N/A
Input Filter Response	Configurable: 8Hz, 12Hz, 16Hz, 40Hz, 200Hz, 1000Hz	Configurable: 2.3Hz, 4Hz, 4.7Hz, 24Hz, 28Hz
A/D Conversion Type	Sigma Delta	Sigma Delta
A/D Conversion Time	(Assumes 2 ADC's running in parallel, no CJC or lead resistance) 10ms per Channel 4 Channels = 40ms (1KHz filter) 127ms per Channel 4 Channels = 508ms (8Hz filter) Channels that are disabled are not scanned, shortening scan time.	15 msec @ 28 Hz to 120 msec @ 2.3 Hz
Maximum Voltage Input	±14.5 VDC continuous	N/A
Connector Type	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.	IC694TBBx32, IC694TBSx32 or IC694TBC032. Sold Separately.
Internal Power Used	400 mA @ 5 V; 350 mA @ 3.3 V	150 mA @ 5 V; 300 mA @ 3.3 V



Networks and Distributed I/O Systems

The RX3i features a variety of communications options for distributed control and/or I/O. Choose from PROFINET Controller, Ethernet EGD, PROFIBUS-DP, Genius and DeviceNet. These communication modules are easy to install and quick to configure.

	IC695ETM001	IC695PNC001	IC695PNS001	IC695CMX128
Product Name	PACSystems RX3i Ethernet TCP/IP 10/100Mbps, two RJ-45 ports with built-in switch	PROFINET Controller (PNC) module, connects a PACSystems RX3i controller to a high-speed PROFINET local area network. It enables the RX3i controller to communicate with IO-Devices on the LAN.	PACSystems RX3i PROFINET Scanner (PNS) module, connects a remote node of 90-30 or RX3i modules to a PROFINET IO-Controller	RX3i Control Memory Xchange Module for Peer to Peer network. 128Megbytes of user shared memory.
Lifecycle Status	Active	Active	Active	Active
Module Type	Ethernet	PROFINET Controller	PROFINET Scanner	Reflective Memory
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1	1	1
Protocol Support	SRT, Ethernet Global Data (EGD), Channels (Client and Server), Modbus TCP (Client and Server)	PROFINET	PROFINET	None Required
Entity Type	Client/Server	Master	I/O Device (Scanner)	Deterministic Peer to Peer. Programmable Interrupt support.
Communication Ports	Two RJ-45 ports one MAC Address	Two RJ-45 and Two SFP Cages (SFPs not included, available separately). 5 MAC addresses.	Two RJ-45 and Two SFP Cages (SFPs not included, available separately). 5 MAC addresses.	
Bus Speed	10/100Mbaud	10/100/1000Mbaud	10/100/1000Mbaud	Network link speed of 2.1 Gigabits/sec. Network transfer rate of 43 Mbyte/s (4 byte packets) to 174 Mbyte/s (64 byte packets)
I/O Device Update Rate	N/A	Configurable: 1 ms to 512 ms	Configurable: 1 ms to 512 ms	
Maximum I/O Memory	N/A	128 Kbytes of combined input/output memory per PROFINET Controller	2880 bytes total: 1440 bytes of input data, 1440 bytes of output data	
System Maximum Limits	N/A	Up to 4 PNC001 per CPU IO 64 IO-Devices per Network 255 IO-Devices across 4 PROFINET controllers per CPU 256 PROFINET Slots per device 2048 Number of PROFINET Submodules per CPU	1 PNS per rack 32 input status bits and 32 output control bits	
Network Distance	Network Dependent	100 meters for cooper Up to 70,000 meters with Fiber	100 meters for cooper Up to 70,000 meters with Fiber	Multimode Fiber up to 300 meters between nodes. 10Km when HUB is used
Bus Diagnostics	Yes	Yes	Yes	Network error detection.
Number of Drops Supported	Network Dependent	64 Drops 256 Subslots	Supports number of modules allowed per rack Does not support LRE for Series 90-30 expansion racks	256
Message Size	N/A	N/A	N/A	Up to 128 Mbytes reflective memory with parity. Dynamic packet sizes of 4 to 64 bytes, automatically controlled by the CMX module
Connector Type	Two RJ-45	Two RJ-45 and two optional SFP plug connectors for copper or fiber (single or multimode) connections	Two RJ-45 and two optional SFP plug connectors for copper or fiber (single or multimode) connections	Fiber optic LC type, conforms to IEC 61754-20; Zirconium ceramic ferrule; Insertion loss 0.35 dB (maximum); Return loss -30 dB
Internal Power Used	840 mA @ 3.3 VDC; 614 mA @ 5 VDC	3.3 V: 0.5 A with no SFP devices installed 1.2 A maximum (two SFP devices installed, 0.35 A per SFP device) 5 V: 1.5 A maximum	3.3 V: 0.5 A with no SFP devices installed 1.2 A maximum (two SFP devices installed, 0.35 A per SFP device) 5 V: 1.5 A maximum	660 mA @ +3.3 VDC 253 mA @ +5 VDC



Networks and Distributed I/O Systems

The RX3i features a variety of communications options for distributed control and/or I/O. Choose from Ethernet EGD, PROFIBUS-DP, Genius and DeviceNet. These communication modules are easy to install and quick to configure.

	IC695PBM300	IC695PBS301	IC694BEM331	IC694DNM200
Product Name	PACSystems RX3i PROFIBUS Master Module, Supports DPV1 Class 1 and Class 2.	PACSystems RX3i PROFIBUS Slave Module, Supports DPV1 Class 1 and Class 2.	PACSystems RX3i Genius Bus Controller	PACSystems RX3i DeviceNet Master Module
Lifecycle Status	Active	Active	Active	Active
Module Type	PROFIBUS Master	PROFIBUS Slave	Genius Bus Controller	DeviceNet Master
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions	CPU Rack Only
Number of Slots Module Occupies on Backplane	1	1	1	1
Protocol Support	PROFIBUS DPV1	PROFIBUS DPV1	Genius	DeviceNet
Entity Type	Master	Slave	Master	Master
Communication Ports	PROFIBUS DB-9 connector	PROFIBUS DB-9 connector	Screw Terminal	Screw Terminal
Bus Speed	12Mbaud	12Mbaud	153.6Kbaud	500Kbaud
I/O Device Update Rate				
Maximum I/O Memory				
System Maximum Limits				
Network Distance	Baud Rate Dependent. Supports all standard data rates (9.6 kBit/s, 19.2 kBit/s, 93.75 kBit/s, 187.5 kBit/s, 500 kBit/s, 1.5 MBit/s, 3 MBit/s, 6 MBit/s and 12 MBit/s)	Baud Rate Dependent. Supports all standard data rates (9.6 kBit/s, 19.2 kBit/s, 93.75 kBit/s, 187.5 kBit/s, 500 kBit/s, 1.5 MBit/s, 3 MBit/s, 6 MBit/s and 12 MBit/s)	7500 feet (2286 meters) at 38.4 Kbaud; 4500 feet (1371 meters) at 76.8 Kbaud; 3500 feet (1066 meters) at 153.6 Kbaud extended; 2000 feet (609 meters) at 153.6 Kbaud standard. Maximum length at each baud rate also depends on cable type.	500Kbaud 100 meters to 125Kbaud 500 meters. Maximum length at each baud rate also depends on cable type.
Bus Diagnostics	Yes, Slave Status Bit Array Table, Network Diagnostic Counters, DP Master Diagnostic Counters, Firmware Module Revision, Slave Diagnostic Address	Yes, Alarms	Yes	Yes
Number of Drops Supported	Up To 125 (Requires repeater every 25 nodes)	N/A	32	64
Message Size	244 bytes of input and 244 bytes of output for each slave. Not to exceed 3584 bytes input and 3584 bytes outputs total for the system.	244 bytes of input and 244 bytes of output	128 bytes	127 bytes
Connector Type	PROFIBUS Connector	PROFIBUS Connector	Screw Terminal	Screw Terminal
Internal Power Used	420 mA @ 5 VDC	420 mA @ 5 VDC	300 mA @ 5 VDC	300 mA @ 5 VDC



Co-Processor and Serial Communications Modules

RX3i features a wide range of Specialty Modules to meet all of your application needs. From temperature controls, high-speed counters, I/O processors, coprocessors, to PID auto-tuning modules, these Specialty Modules are designed to meet the demand for versatile industrial solutions.

	IC695CMM002	IC695CMM004	IC695PRS015	HE693ASC900
Product Name	Two Port Serial Module	Four Port Serial Module	Pressure Transducer Module supporting Honeywell LG1237 Smart Sensors	Horner ASCII Basic Module
Lifecycle Status	Active	Active	Active	Active
Module Type	Serial Communications 2 Isolated Serial Ports	Serial Communications 4 Isolated Serial Ports	Serial Communications	Serial Communications 4 Isolated Serial Ports ASCII Basic Co-Processor
Backplane Support	Universal Backplane Only. Uses PCI Bus	Universal Backplane Only. Uses PCI Bus	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Protocols Supported	Serial Read/Write Modbus Master/Slave DNP 3.0 Master/ Slave CCM Slave and Custom Protocols	Serial Read/Write Modbus Master/Slave DNP 3.0 Master/ Slave CCM Slave and Custom Protocols	Pressure Transducer Honeywell LG1237 Smart Pressure Transducer sensors (Up to 15 sensors)	N/A
Programming Languages	None required. Communications set up in Proficy Machine Edition	None required. Communication set up in Proficy Machine Edition		BASIC
Program Storage	FLASH	FLASH	FLASH	EEPROM
Communication Ports	(2) Isolated RS-232 or RS-485/422	(4) Isolated RS-232 or RS-485/422	(1) RS-485	RS-232, RS-232/485
Network Data Rate	Selectable Baud Rates: 1200, 2400, 4800, 9600, 19.2K, 38.4K, 57.6K, 115.2K	Selectable Baud Rates: 1200, 2400, 4800, 9600, 19.2K, 38.4K, 57.6K, 115.2K	375K baud	N/A
Internal Power Used	0.7 Amps maximum @ 3.3 VDC 0.115 Amps maximum @ 5 VDC	0.7 Amps maximum @ 3.3 VDC 0.150 Amps maximum @ 5 VDC	0.7 Amps maximum @ 3.3 VDC 0.115 Amps maximum @ 5.0 VDC	375 mA @ 5 VDC



Motion Control (High Speed Counting)

The High Speed Counters can be used for a wide range of applications. The following types are supported.

Type A - Up or Down-Independent Pulse-4 counters

Type B - Both Directions-A QUAD B Encoder Inputs-2 Counters

Type C - Difference Between 2 changing values-A QUAD B Encoder Inputs -1 Counter

Type D - provides homing capability with count inputs and a Home Marker input. In A quad B mode, the counter detects quadrature errors

Type E - Pre-defined Counter Type that occupies two of the module's internal counters, primarily a down counter, but can handle up counts to account for A quad B jitter

Type E counter counts down to zero, it uses a second counter block to turn on a dedicated output for a configurable time. Type E can be set up for sequenced strobing, which links all four strobes on so that they are all triggered by strobe input 1

Type Z - Two regular Clock inputs, a software controlled Preload and a special Clock Input Z. The Z input triggers a store of the Accumulator value to the Strobe 1 register. After the store, the counter can optionally reset the Accumulator to 0. It can then either restart immediately or after wait until the Clock Input Z is no longer set User-Defined Counter Type - Create a customized counter type by selecting High-Speed Counter features that are suited to the application. This counter type provides a Clear input that can be used to immediately reset the Accumulator to the starting value.

	IC694APU300	IC695HSC304	IC695HSC308	IC694APU305
Product Name	PACSystems RX3i High Speed Counter	PACSystems RX3i High Speed Counter	PACSystems RX3i High Speed Counter	PACSystems RX3i I/O Processor Module
Lifecycle Status	Active	Active	Active	Active
Module Type	High Speed Counter (*Enhanced Mode support: 1MHz input frequency, expanded filtering, single ended, differential encoders, 32 bit counters, Z counter and windowing)	High Speed I/O Processing (4 counters) Module supports High Speed Counting, PLS (Programmable Limit Switch), Camming, Input Interrupts and Pulse Width Timing	High Speed I/O Processing (8 counters) Module supports High Speed Counting, PLS (Programmable Limit Switch), Camming, Input Interrupts and Pulse Width Timing	I/O Processor Module
Backplane Support	No Backplane Restrictions	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Input/Output Type	Positive Logic	Positive Logic	Positive Logic	N/A
Off State Leakage Current	10 µA per point	200 µA	200 µA	10 µA per point
Output Protection	3 Amp Fuse for all points, Enhanced Module will have ESCP protection	1.5 A maximum per channel, 10.5 A maximum per module	1.5 A maximum per channel, 10.5 A maximum per module	5 A Fuse for all points
Counter Operation	Type A, Type B, and Type C Enhanced Mode Type Z	Type A, Type B, Type C, Type D, Type E, Type Z and User-Defined Counter	Type A, Type B, Type C, Type D, Type E, Type Z and User-Defined Counter	Gray Code Encoder or A Quad B Encoder every 500 microseconds
CPU Interrupt Support	No	Yes	Yes	N/A
PLS and Camming Support	No	Yes	Yes	N/A
Input Filters (Selectable)	High Frequency Filter - 2.5 µs; Low Frequency Filter - 12.5 ms; *Enhancement Mode: 5 ms, 500 µs, 10 µs and no filter	30 Hz, 5 KHz, 50 KHz, 500 KHz, 5 MHz	30 Hz, 5 KHz, 50 KHz, 500 KHz, 5 MHz	N/A
Count Rate	High Frequency - 80 kHz; Low Frequency - 20 Hz; *Enhanced Mode Up to 1MHz with 2MHz internal Oscillator	High Frequency 1.5 MHz (internal 2 MHz oscillator)	High Frequency 1.5 MHz (internal 2 MHz oscillator)	30 kHz (Absolute Encoder) 200 kHz (A Quad B Encoder)
Counter Range	-65,535 to 65,535 ; *Enhanced Mode -2,147,483,648 to 2,147,483,647 with roll over detection	-2,147,483,648 to 2,147,483,648	-2,147,483,648 to 2,147,483,648	N/A
Selectable On/Off Output Presets	Each Counter has 2 present points, On and Off; *Enhanced Mode up to 4 configurable outputs	Each Counter has 4 present points, On and Off	Each Counter has 4 present points, On and Off	N/A
Counters per Timebase	Each counter stores the number of counts that have occurred in a specified time. A timebase value measurement from 1 ms to 65535 ms is configurable.	A Timebase from 100 nanoseconds to 429,496 milliseconds can be selected for each counter.	A Timebase from 100 nanoseconds to 429,496 milliseconds can be selected for each counter.	N/A
Strobe Register	Each counter has one or more strobe registers that capture the current accumulator value when a strobe input transition in the direction selected during the last configuration of the module. (12) 5 VDC or 10 to 30 VDC	Each counter has one or more strobe registers that capture the current accumulator value when a strobe input transition in the direction selected during the last configuration of the module.	Each counter has one or more strobe registers that capture the current accumulator value when a strobe input transition in the direction selected during the last configuration of the module.	N/A
Local Fast Inputs		(8 inputs) 5 VDC nominal: 4.7 VDC to 5.5 VDC 12 to 24 VDC nominal: 10 VDC to 26.4 VDC Inputs are mapped to any counter or to the controller as interrupts.	(16 inputs) 5 VDC nominal: 4.7 VDC to 5.5 VDC 12 to 24 VDC nominal: 10 VDC to 26.4 VDC Inputs are mapped to any counter or to the controller as interrupts.	(12) 8.0 VDC (non-VTTL), 1.5 VDC (TTL)
Local Fast Outputs	(4) 10 to 30 VDC @ 500 mA maximum; *Enhanced Mode: 1.5 A with ESCP 4.75 to 6 VDC @ 20 mA maximum	(7 outputs) 4.7 to 40 VDC 1.5 A maximum per channel, 10.5 A maximum per module Outputs can be used by the counters or as standard outputs from the controller.	(14 outputs) 4.7 to 40 VDC 1.5 A maximum per channel, 10.5 A maximum per module Outputs can be used by the counters or as standard outputs from the controller.	Continuous Output Current (10*V30 VDC supply) 1.0 A (each output 1-V4) 0.5 A (each output 5-V8)
Connector Type	Terminal Block (20 screws), included with module.	IC694TBBx32 or IC694TBSx32. Sold Separately.	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.
Internal Power Used	250 mA @ 5 VDC	64 mA maximum @ 5 V; 457 mA maximum @ 3.3 V	94 mA maximum @ 5 V; 561 mA maximum @ 3.3 V	360 mA @ 5 VDC



PACMotion Servo Control

The PACMotion controller is a versatile servo motion controller that combines the benefits of a highly integrated motion and machine logic solution with the performance, flexibility and scalability required for advanced machine automation. PACMotion is designed to deliver unsurpassed machine productivity required for today's high-speed machines and lean manufacturing environments. The 4-axis servo motion controller is built on a high performance hardware platform, with a new enhanced motion engine, operating system, and open standard integrated programming paradigm. Add to that world-class reliability of FANUC servos and you have a motion system designed to give you the best productivity and accuracy possible. Please see GE Intelligent Platforms Motion Solutions Catalog GFA-483 for more information about motion offerings.

IC695PMM335

Product Name	PACMotion Module
Lifecycle Status	Active
Module Type	Servo Motion
Backplane Support	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1
Motion Path Planning	1 ms, Consistent update regardless of the number of axes in the system
Position Loop Update Rate	500 μ s, All axes in the RX3i rack are updated simultaneously
Velocity Loop Update Rate	125 μ s, All axes in the RX3i rack are updated simultaneously
Torque Loop Update Rate	62.5 μ s, All axes in the RX3i rack are updated simultaneously
Controlled Axes/Module	4 β i, β HVi or aHVi series servos are supported via a fiber optic interface
Master Axes/Module	1, Can be a virtual time-based or incremental encoder master
Servo Command Interface	Fiber Optic 50 Mb/s FANUC Serial Servo Bus (FSSB)
Fiber Terminal Block Cable Length	Max. 100 meters between nodes 400 meters maximum for a 4 axis system
Maximum Axes per RX3i	DC Power Supplies: 40 + 10 master axes (Requires 16 slot backplane, CPU and 4 DC power supplies) AC Power Supplies: 32 + 8 master axes (Requires 16 slot backplane, CPU and 3 AC power supplies)
Position Resolution	aHVi Series 1,048,576 counts/rev, β i and β HVi Series 65,536 or 131,072 counts/rev. β 2i and larger motors support the higher resolution.
Feedback Type	Incremental/Absolute Serial Encoder. Optional battery backup required for absolute feedback mode.
Faceplate I/O	24V General Purpose Inputs: 4 optically isolated; source/sink 24V High-Speed Inputs: 2 optically isolated; source/sink Open circuit detection; can be used to connect a quadrature master encoder (500 kHz max) 24V General Purpose Inputs/Outputs: 2 optically isolated; source/sink 125 mA maximum output current each "Connecto" Plug-on Screw Terminal
Floating Point Support	Yes, Double precision IEEE 754.
Module Hot Insertion/Removal	Yes
Cam Profiles per Module	256 at one time. Up to 2048 profiles can be stored in the RX3i file system for use by any module.
Synch/Delayed Start	Up to 8 axes Axes can be on any module and are synchronized over the backplane.
High Speed Position Capture	\pm 2 Inputs per axis: \pm 1 count = 10 μ s jitter
Connector Type	Plug-on Screw Terminal and Fiber
Internal Power Used	5 VDC 0.45A @ 5 VDC; 1.1A & 3.3 VDC



PACMotion I/O Fiber Terminal Block

The optional Fiber Terminal Block enables PACMotion controller to connect remote I/O over a fiber cable. The Fiber Terminal Block is DIN-rail mounted and can be up to 100 meters away from the PACMotion module. The module is configurable per point for 5 VDC, 24 VDC and analog I/O. The Fiber Terminal Block provides a unique ID that prevents connection to wrong PACMotion modules. The module supports up to 5 incremental encoders without marker or 4 encoders with marker pulse.

IC695FTB001

Product Name	PACMotion I/O Fiber Terminal Block
Lifecycle Status	Active
Module Type	I/O Terminal Block for PACMotion
Mounting/Dimensions	35 mm DIN-rail (5.56 W x 4.94 H x 2.46 D inches; 141.2 W x 125.5 H x 62.5 D mm)
Interface to PACMotion Module	Fiber Optic Cable. Maximum cable length is 100 meters; Interface uses a unique ID for each PMM/FTB pair to prevent cross-connection.
Power Requirements	19.2 VDC —28.8 VDC; 0.45 Amps @ 24 V
24 V Outputs (differential)	Eight optically isolated; source; open load & short detection. 2 groups of 4; 0.5 A max. per point; 4 A max. per group
24 V General Purpose Inputs	Sixteen optically isolated; source/sink 4 groups of 4
5 V Outputs (differential)	Four RS422 Line Driver with short circuit protection; 48 mA max.
5 V Inputs (differential/single-ended)	Six RS422 / RS485 Line Receiver with fault detection
5 V Inputs (differential)	Six RS422 / RS485 Line Receiver with fault detection
Analog Inputs	Two, ±10V differential 14 bit resolution
Analog Outputs	Two, ±10V differential 14 bit resolution
24 V Power Output	Reverse polarity protected by replaceable fuse
5 V Power Output	0.5 amp max. electronic overload protected
Quad Encoder Open Circuit Detection	Yes
I/O Function Assignment	Configurable I/O functions are assigned during module hardware configuration
Terminal Header Options	IC694TBxx32



Motion Control (Servo Control)

Motion control integrated into the RX3i fosters high performance point-to-point applications. GE Motion Control modules can be flexibly applied to a variety of digital, analog, and stepper motion applications.

	IC694DSM324	IC694DSM314
Product Name	PACSystems RX3i Digital Servo Module, 4-Axis (Fiber Optic Interface to Amplifiers)	PACSystems RX3i Digital Servo Module, 4-Axis
Lifecycle Status	Active	Active
Module Type	Servo Motion	Servo Motion
Backplane Support	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1
Drive	Beta i Series Digital Servos	Alpha and Beta Series Digital and Analog Servos
Drive Interface	Fiber Optic, Up to 100 meters between amplifiers with total length of 400 meters.	Digital for Alpha and Beta Series; ±10 V velocity or torque command for analog
Axes	4 Digital	2 Digital and 1 Analog or 4 Analog
Master Encoder Support	Incremental Master (1Mhz)	Incremental Master (1Mhz)
Electronic Cam	Yes	Yes
Velocity Feed-Forward	Yes	Yes
Encoder Feedback (Serial)	Yes	Yes
Temposonic Feedback	Yes	Yes
Number of Programs	15 Kbytes (10 + 40 Subroutines)	15 Kbytes (10 + 40 Subroutines)
User Memory (Number of Programs)	15 KBytes	15 KBytes
Feedback Inputs	3	3
Encoder Input Type/Maximum Rate	TTL Diff/Single, 175kHz	TTL Diff/Single, 175kHz
Analog Inputs	2	4 - In Digital Mode 8 - In Analog Mode
Analog Outputs	2	4 - In Digital Mode 0 - In Analog Mode
Internal Power Used	1360 mA @ 5 VDC	1300 mA @ 5 VDC



Power Measurement Modules

The Power Transducer Module (PTM) and Power Synchronization and Measurement (PSM) module measure and calculate critical data for control of electrical power systems and synchronization of power grids. Both the PTM and PSM connect to user supplied current and potential transformers, which translate power grid signals to proportionate, low-level signals for measurement and analysis. The PTM module is not intended to provide a protective relay function or be used for energy billing purposes. The PSM module provides ANSI protective relay calculations and revenue grade monitoring for a complete genset, paralleling switchgear or infrastructure management solution. Both the PTM and PSM consist of a processing module that plugs into the PLC backplane, an interface module for field wiring connections, and cables to interconnect the two modules. The PTM and PSM can be used with Wye or Delta type three-phase power or with single-phase power systems.

	IC693PTM101	IC694PSM001														
Product Name	Power Transducer Module Processing Module interface board (a panel mounted circuit board). This board interfaces between the Power Transducer module and the input transformers (current and potential), 1.0 meter Interface cable that connects the module to the Interface board.	Power Synchronization and Measurement Module and Interface Module (a panel mounted terminal block). The interface module translates power grid signals from external, user supplied potential and current transformers (PT's and CT's) to low voltage signals suitable for the processing module. 2.0 meter Interface cables connect the processing module to the Interface module.														
Lifecycle Status	Mature	Active														
Module Type	Power Transducer Modules	Power Synch and Measurement Module														
Input Voltage Range	10-120 VAC (nominal)	20-600 VAC (nominal)														
Power Measurement Configurations	<table border="1"> <tr> <td>Grids</td> <td>Circuits</td> </tr> <tr> <td>1</td> <td>0</td> </tr> <tr> <td>0</td> <td>up to 4</td> </tr> </table>	Grids	Circuits	1	0	0	up to 4	<table border="1"> <tr> <td>Grids</td> <td>Circuits</td> </tr> <tr> <td>2</td> <td>0</td> </tr> <tr> <td>1</td> <td>up to 3</td> </tr> <tr> <td>0</td> <td>up to 6</td> </tr> </table>	Grids	Circuits	2	0	1	up to 3	0	up to 6
Grids	Circuits															
1	0															
0	up to 4															
Grids	Circuits															
2	0															
1	up to 3															
0	up to 6															
Current Input Range	0 to 7.5 Amps RMS (5 A RMS nominal)	0 to 7.5 Amps RMS (5 A RMS nominal)														
Frequency Range	35Hz to 70Hz	40Hz to 70Hz														
Output Rating	N/A	150 VAC/VDC, 1 A														
Number of Outputs	0	1 (provided as redundant, isolated, solid-state contacts)														
Data	<p>Data availability</p> <ul style="list-style-type: none"> Data calculation rate: 20ms @ 50Hz, 16.67ms @ 60Hz Data latency: 15ms @ 50Hz, 16.67ms @ 60Hz <p>Measured Data</p> <ul style="list-style-type: none"> RMS voltage of phase A, B, and C (in Volts x 10) RMS currents of phase A, B, C, and Neutral (in Amperes x 1000) for each grid DC component of measured RMS voltages (in Volts x 10) Frequency of phase A grid 1 (in Hz x 100) Phase angle between phase A grid 1 and phase A grid 2 (in degrees x 10) <p>Power and Energy Data</p> <ul style="list-style-type: none"> Active and reactive power reported per phase and total in Watts, Volt-Amperes- Reactive (VAR) Active and reactive total energy consumption in Watt-Seconds and Volt-Amperes-Reactive-Seconds (updated once per second), re-settable by the user Total power factor Average real and reactive power consumption (sliding 15 minute window updated once per second) 	<p>Data availability</p> <ul style="list-style-type: none"> Data measurement rate: 20ms @ 50Hz, 16.67ms @ 60Hz. Data latency: 8ms <p>Measured Data</p> <ul style="list-style-type: none"> RMS voltage of phase A, B, and C (in Volts x 10) RMS currents of phase A, B, C, and Neutral (in Amperes x 1000) for each grid DC component of measured RMS voltages (in Volts x 10) Frequency of phase A grid 1 and phase A grid 2 (in Hz x 100) Phase angle between phase A grid 1 and phase A grid 2 (in degrees x 10) <p>Calculated Data</p> <ul style="list-style-type: none"> Real and reactive power reported per phase and total in Watts, Volt-Amperes-Reactive (VAR) Real and reactive total energy consumption, integrated over the past 1-second, in Kilo Watt-Hours (kWh) and Kilo Volt-Amperes-Reactive-Hours (kVARh) Total power factor Average real and reactive power consumption (sliding 15 minute window updated once per second) 														
Status and Diagnostics	<ul style="list-style-type: none"> Module Heartbeat (indicates module health) Utility Phase A voltage present Phase polarity valid Voltage measurements valid Current measurements valid 	<ul style="list-style-type: none"> Module Heartbeat (indicates module health) Field connection OK Any grid alarm (single bit indication of power grid health) Grid Voltage fault Grid Current fault Mixed Polarity fault ANSI Protection Relay Calculations Grid Synchronization (ANSI 25) <ul style="list-style-type: none"> Phase Shift OK Voltage Difference OK Frequency Difference OK Close Relay OK Under Voltage alarm (ANSI 27) Reverse Power alarm (ANSI 32) Negative Sequence alarm (ANSI 46) Over Current alarm (ANSI 50) Over Voltage alarm (ANSI 59) VA Imbalance alarm (ANSI 60) Under Frequency alarm (ANSI 81U) Over Frequency alarm (ANSI 81O) 														
Internal Power Used	400 mA @ 5 VDC	190 mA @ 5 VDC														



RX3i Pneumatic Module

This IC693MDL760 output module provides eleven pneumatic outputs and five 24 VDC sourcing outputs. For each pneumatic output, the module contains an internal 3-way solenoid-actuated valve and an associated output fitting, which is located on the front panel. When an output is turned ON, its internal valve connects a user supplied pressure source (100 psi maximum) to the output fitting. The pressure source is connected to the fitting on the bottom of the module. When the output is turned OFF, the valve’s output port is vented to atmosphere inside the module. Solenoid power is supplied from an external 24 VDC source to the “DC Outputs” connector on the front panel.

IC693MDL760

Product Name	RX3i Solenoid Module
Lifecycle Status	Active
Number of Points	(11) Pneumatic Outputs (5) 24 VDC Outputs
Pneumatic Outputs	11
Supply Pressure	100 PSI
Pressure Drop	25 psi max.@ 0.25scfm
External Solenoid Power	21.6-26.4 VDC, 24 VDC nominal
ON Response Time/Off Response Time	12ms max. ON 12ms max. OFF
Solenoid Inrush Current	33 mA/valve @ 24 VDC
Solenoid Holding Current	13 mA/valve @ 24 VDC
Output Fitting	Threaded for 10-32 adapter, 1/16" hose barb provided
Supply Fitting	Threaded for 10-32 adapter, 1/8" hose barb provided
Load Current per Point	0.5A @ 30 VDC per point, 2.0A total for all five points
Response Time (ms)	0.5 on/0.5 off
Output Type	Transistor
Polarity	Positive
Internal Power Used	75 mA from 5 VDC bus (solenoid LEDs are powered from external power source)



Expansion Modules for Local and Remote I/O

The RX3i supports various expansion options for local and remote I/O to optimize configurations. The RX3i can be expanded up to 8 expansion bases using local remote expansion module. The RX3i also supports Ethernet remote I/O using the RX3i Ethernet Network Interface module (IC695NKT001) Series 90-30 Ethernet Network Interface module (IC693NIU004) for more distributed I/O.

	IC695NKT001	IC693NIU004	IC695LRE001
Product Name	PACSystems RX3i Ethernet Remote I/O Expansion Kit. Kit includes a NIU001 with two built-in serial ports and ETM001	PACSystems RX3i Ethernet Remote I/O Expansion (Slave)	PACSystems RX3i Expansion Module
Lifecycle Status	Active	Active	Active
Module Type	Ethernet Communications (Supports redundant Ethernet modules)	Ethernet Communications	High Speed Serial Expansion Module
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Compatible with Series 90-30 bases only	Universal Backplane Only
Number of Slots Module Occupies on Backplane	3 (2 for NIU and 1 for Ethernet module)	N/A	No I/O slot used
Built-in Communication Ports	RJ-45 with built-in switch. 1 RS-485 port and one RS-232 port. Supports SNP, Serial I/O, Modbus Slave and Modbus Master	N/A	N/A
I/O Discrete Points	2048 Inputs/2048 Outputs maximum	2048 Inputs/2048 Outputs maximum	N/A
I/O Analog Points	1264 Inputs and 512 Outputs maximum	1264 Inputs and 512 Outputs maximum	N/A
User Logic Memory	5Kbytes of local logic	No local logic	N/A
Network Data Rate	10/100Mbit ports (RJ-45)	10/100Mbit ports (RJ-45)	1 Mbaud
Entity Type	Slave	Slave	Master
Network Distance	Network Dependent	Network Dependent	Up to 700 feet (213 meters)
Bus Diagnostics	Supported	Supported	Yes
Number of Drops Supported	Network Dependent Each Ethernet NIU can also support up to 7 additional local I/O racks (IC694CHSxxx)	Network Dependent Each Ethernet NIU can also support up to 7 additional local I/O racks (IC694CHSxxx)	Supports 7 local expansion racks. Discrete I/O: Maximum 320 In, 320 Out, Analog I/O: Maximum 160 In, 80 Out per base
Internal Power Used	1250 mA @ 3.3 VDC; 1000 mA @ 5 VDC for NIU controller and 840 mA @ 3.3 VDC; 614 mA @ 5 VDC for each Ethernet module	1.4 Amps @ 5 VDC	132 mA @ 5 VDC

Accessories

IC694TBB032	High Density 32 Point Terminal Block Box Style	Active
IC694TBB132	High Density 32 Point Terminal Block Box Style with Extended Shroud for Large Wiring Bundles	Active
IC694TBS032	High Density 32 Point Terminal Block Spring Style	Active
IC694TBS132	High Density 32 Point Terminal Block Spring Style with Extended Shroud for Large Wiring Bundles	Active
IC694TBC032	High Density 32 Point Terminal Block with a 40 pin Fujitsu connector. Compatible with DC Inputs, Analog Modules only. Not compatible with DC or AC output modules.	Active
IC694ACC310	Filler Module, Blank Slot	Active
IC694ACC311	Terminal blocks, 20 terminals (qty 6) for IC694xxx low density modules	Active
IC695ACC600	RX3i Cold Junction Compensation Kit (Contains 2 CJs) for Universal Analog and Thermocouple Input Modules	Active
IC698ACC701	Lithium Batter pack that installs in CPU for CPU310 and CMU310 only (28 days of continuous battery backup)	Active
IC693ACC302	External High capacity battery pack. (1.3 years of continuous battery backup for CPU310/CMU310 and 1 month for CPU320/CRU320.)	Active
IC690RBK001	Rechargeable battery kit. Includes battery (IC690RBT001) and battery charger (IC690CRG001). The rechargeable battery is compatible with PAC controllers CPU310,CPU315, CPU320 and CRU320 only. Also compatible with Series 90-30 and Series 90-70 CPUs.	Active
IC690CRG001	Battery charger. Compatible with rechargeable battery (IC690RBT001) only. The rechargeable battery is compatible with PAC controllers CPU310,CPU315, CPU320 and CRU320 only. Also compatible with Series 90-30 and Series 90-70 CPUs.	Active
IC690RBT001	Rechargeable battery is compatible with IC690CRG001 battery charger only. The rechargeable battery is compatible with PAC controllers CPU310, CPU315, CPU320 and CRU320 only. Also compatible with Series 90-30 and Series 90-70 CPUs., Series 90-30 and Series 90-70.	Active
IC690ACC001	Real Time Clock Battery for CPE305 and CPE310	Active
IC695ACC400	CPE305 and CPE310 CPU Battery-less Energy Pack for backing up dynamic data	Active
IC695CBL001	Energy Pack Cable	Active
IC690ACC901	Mini-Converter Kit with cable (RS-485/RS-232)	Active
IC690ACC903	RS-485 Port Isolator	Active
IC693CBL316	RS-232 cable for RX3i CPE305 programming port and also the Station Manager Cable for the Ethernet ETM001	Active
IC690CDR002	User Manuals, InfoLink CD-ROM Documentation, single-user license	Active
IC693ACC307	I/O Bus Terminator Plug	Active
IC693ACC311	Series 90-30 style IC693 I/O modules Terminal Blocks, 20 terminals (qty 6)	Active

External Power Supplies

IC690PWR024	24 VDC, 5 Amp Output Power and 120/230 VAC Input Power Power Supply	Active
IC690PWR124	24 VDC, 10 Amp Output Power and 120/230 VAC Input Power Power Supply	Active

Terminal Block Quick Connect

Terminal Block Quick Connect (TBQC) for selected I/O modules enables the user to easily connect interposing terminal blocks. The TBQC consists of an I/O faceplate adapter that includes a 24 pin Fujitsu male connector (the faceplate replaces the 20 screw terminal connector on front of I/O module, not compatible with the high density 36 screw terminals), cable and interposing terminal block.

TBQC I/O Module Face Plate Adapter

IC693ACC334	I/O module face plate adapter for 20 screw type I/O modules. Faceplate provides a 24 pin male Fujitsu connector.	Active
-------------	--	--------

TBQC Interposing Terminal Block

IC693ACC329	Interposing terminal block base for IC694MDL645, IC694MDL646, and IC694MDL240. The base can also be used with any 20 point terminal discrete or analog modules not listed.	Active
IC693ACC330	Interposing terminal block base for IC694MDL740 and IC694MDL742	Discontinued
IC693ACC331	Interposing terminal block base for IC694MDL741	Discontinued
IC693ACC332	Interposing terminal block base for IC694MDL940	Active
IC693ACC333	Interposing terminal block base for IC694MDL340	Active
IC693ACC337	Interposing terminal block base for IC693MDL654/655/752/753 and IC694MDL654/655/752/753	Active

TBQC Cables

IC693CBL327	Cable, Left Side, One -24 Pin 90 Degree Connector, 3 Meter. Cable has a connector on only one end and open on the other. Cable used with TBQC I/O Face Plate Adapter or Fujitsu style I/O modules.	Active
IC693CBL328	Cable, Right Side, One -24 Pin 90 Degree Connector, 3 Meter. Cable has a connector on only one end and open on the other. Cable used with TBQC I/O Face Plate Adapter or Fujitsu style I/O modules.	Active
IC693CBL329	Cable, Left Side, One -24 Pin 90 Degree Connector, 1 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active
IC693CBL330	Cable, Right Side, One -24 Pin 90 Degree Connector, 1 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active
IC693CBL331	Cable, Left Side, One -24 Pin 90 Degree Connector, 2 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active
IC693CBL332	Cable, Right Side, One -24 Pin 90 Degree Connector, 2 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active
IC693CBL333	Cable, Left Side, One -24 Pin 90 Degree Connector, 0.5 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active
IC693CBL334	Cable, Right Side, One -24 Pin 90 Degree Connector, 0.5 Meter. from TBQC I/O Face Plate Adapter to TBQC Interposing Terminal Block.	Active

High Density Terminal Block Quick Connect (32 point I/O terminals)

High Density Terminal Block Quick Connect (TBQC) for selected I/O modules enables the user to easily connect interposing terminal blocks. The HDTBQC consist of a I/O module terminal block with a 40 pin Fujitsu male connector, cable and interposing terminal block. The HDTBQC is compatible with modules that accept IC694TBC032 (24 VDC discrete inputs and analog input and output modules. The HDTBQC is not compatible with discrete output modules).

HDTBQC I/O Module Face Plate Adapter

IC694TBC032	High-density, 36-point, terminal block with cable connector. IC695ALGxxx, IC69xMDL660 and IC694MDL664 modules only. Discrete output modules not supported.	Active
-------------	---	--------

HDTBQC Interposing Terminal Block

IC694RTB032	High-density remote base, 36-point, with shield ground lug and removable terminal blocks. IC695ALGxxx, IC69xMDL660 and IC694MDL664 modules only. Discrete output modules not supported.	Active
-------------	--	--------

HDTBQC Interface Cables

IC694CBL005	Shielded 0.5 meter cable with termination on both ends. IC694TBC032 and IC694RTB032 only.	Active
IC694CBL010	Shielded 1.0 meter cable with termination on both ends. IC694TBC032 and IC694RTB032 only.	Active
IC694CBL030	Shielded 3.0 meter cable with termination on both ends. IC694TBC032 and IC694RTB032 only.	Active
IC694CBL130	Shielded 3.0 meter cable with termination on one end that connects to the IC694TBC032 terminal block. The other end of the cable is non-terminated wires.	Active

RMX and CMX Reflective Memory Fiber Optic Cables

Simplex LC to LC connector, Fiber-Optic Cable – Multimode 62.5 Micron core.

Simplex (single) cabling is used for daisy chaining Tx to Rx to/from another node until final device circles back to beginning node.

Each CMX module requires two Simplex cables per module.

CBL-000-F5-000	.5 feet (0.15 m)	Active
CBL-000-F5-001	1 foot (.31 m)	Active
CBL-000-F5-002	5 feet (1.52 m)	Active
CBL-000-F5-003	10 feet (3.04 m)	Active
CBL-000-F5-004	25 feet (7.62 m)	Active
CBL-000-F5-005	50 feet (15.24 m)	Active
CBL-000-F5-006	80 feet (24.40 m)	Active
CBL-000-F5-007	100 feet (30.49 m)	Active
CBL-000-F5-008	150 feet (45.72 m)	Active
CBL-000-F5-009	200 feet (60.98 m)	Active
CBL-000-F5-010	250 feet (76.20 m)	Active
CBL-000-F5-011	350 feet (106.68 m)	Active
CBL-000-F5-012	500 feet (152.15 m)	Active
CBL-000-F5-014	656 feet (200 m)	Active
CBL-000-F5-015	820 feet (250 m)	Active
CBL-000-F5-016	1,000 feet (304.30 m)	Active

Duplex LC to LC connector, Fiber-Optic Cable - Multimode 62.5 Micron core.

Duplex cabling is generally used with RMX system and is also good for CMX module to HUB connections. Duplex has a pair of cables connected together.

Each CMX module requires one Duplex cable per module to a hub.

CBL-000-F6-000	3 feet (0.9144 m)	Active
CBL-000-F6-001	6 feet (1.8288 m)	Active
CBL-000-F6-002	10 feet (3.048 m)	Active
CBL-000-F6-003	16 feet (4.8768 m)	Active
CBL-000-F6-004	32 feet (9.7536 m)	Active
CBL-000-F6-005	66 feet (20.1168 m)	Active
CBL-000-F6-006	98 feet (29.8704 m)	Active
CBL-000-F6-007	164 feet (49.9872 m)	Active
CBL-000-F6-008	230 feet (70.104 m)	Active
CBL-000-F6-009	328 feet (99.9744 m)	Active
CBL-000-F6-010	393 feet (119.7864 m)	Active
CBL-000-F6-011	426 feet (129.8448 m)	Active
CBL-000-F6-012	492 feet (149.9616 m)	Active
CBL-000-F6-013	557 feet (169.7736 m)	Active
CBL-000-F6-014	656 feet (199.9488 m)	Active
CBL-000-F6-015	721 feet (219.7608 m)	Active
CBL-000-F6-016	754 feet (229.8192 m)	Active
CBL-000-F6-017	820 feet (249.936 m)	Active
CBL-000-F6-018	885 feet (269.748 m)	Active
CBL-000-F6-019	984 feet (299.9232 m)	Active

Reflective Memory Interface Modules for PCs

PMC 5565 Reflective Memory PMC Module

PMC-5565PIORC-110000	PMC, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PMC-5565PIORC-111000	PMC, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4 K FIFOs, Single Mode Transmission	Active
PMC-5565PIORC-210000	PMC, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PMC-5565PIORC-211000	PMC, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4 K FIFOs, Single Mode Transmission	Active

PCI 5565 Reflective Memory PCI Module

PCI-5565PIORC-110000	PCI, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PCI-5565PIORC-111000	PCI, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4K FIFOs, Single Mode Transmission	Active
PCI-5565PIORC-210000	PCI, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PCI-5565PIORC-211000	PCI, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4K FIFOs, Single Mode Transmission	Active

PCI Express 5565 Reflective Memory PCIE Module

PCIE-5565RC-100000	PCI Express, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PCIE-5565RC-101000	PCI Express, 2 GIGA Baud RM w/FO Options, 128 Mbyte Memory, 4K FIFOs, Single Mode Transmission	Active
PCIE-5565RC-200000	PCI Express, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4K FIFOs, Multimode Transmission	Active
PCIE-5565RC-201000	PCI Express, 2 GIGA Baud RM w/FO Options, 256 Mbyte Memory, 4K FIFOs, Single Mode Transmission	Active

CMX and RMX Reflective Memory HUB (Contact GE for additional HUB configurations)

HUB-5595-308	DIN-rail Mount Reflective Memory Hub. 21 -32 VDC Power supply, 1x 10BaseT Ethernet, 1x RS232, 8x Multimode Pluggable transceivers	Active
HUB-5595-380	DIN-rail Mount Reflective Memory Hub. 21 -32 VDC Power supply, 1x 10BaseT Ethernet, 1x RS232, 8x Single mode Pluggable transceivers	Active
ACC-5595-208	Rack Mount or Desktop Reflective Memory Hub. Universal power supply, 1x 10BaseT Ethernet, 1x RS232, 8x multimode pluggable transceivers	Active
ACC-5595-280	Rack Mount or Desktop, 8 Single mode Pluggable Transceivers. And no Multimode Pluggable Transceivers	Active

Starter Kits (Only one starter kit per customer per customer site)

IC695STK001	RX3i Controller PACKage 1 Starter Kit includes RX3i with software. (includes one each IC695CPU305, IC695CHS012, IC695LRE001, IC695PSA040, IC695ETM001, IC694ACC300, IC694MDL940 and IC646MPP001.) Limited one RX3i starter kit per customer site.	Active
IC695STK002	RX3i with Control and View. Power PACKage 2 Starter Kit includes RX3i and QuickPanel View 6" STD with software. (includes one each IC695CPU305, IC695CHS012, IC695LRE001, IC695PSA040, IC695ETM001, IC694ACC300, IC694MDL940, IC754VSI06STD, BC646MQP001, IC646MPP001 and DC power supply for QuickPanel) Limited one RX3i starter kit per customer site.	Active
IC695STK003	RX3i, The Complete PACKage with Control, Motion and View. Power PACKage 3 Starter Kit includes RX3i, motion module (Servo and Amplifier sold separately) and QuickPanel View 6" STD with software. (includes one each IC695CPU305, IC695CHS012, IC695LRE001, IC695PSA040, IC695ETM001, IC694DSM314, IC694ACC300, IC694MDL940, IC754VSI06STD, BC646MQP001, IC646MPP001 and DC power supply for QuickPanel) Limited one RX3i starter kit per customer site.	Active
IC695STK004	RX3i Power PACKage 4 Starter Kit includes (one each IC695CPU305, IC695CHS012, IC695PSA040, IC695ETM001, IC646MPP101)	Active
IC695STK005	RX3i Power PACKage 5 Starter Kit includes (one each IC695CPU305, IC695CHS012, IC695PSA040, IC646MPP101)	Active
IC695STK006	RX3i Power PACKage 6 Starter Kit includes (one each IC695CPU305, IC695CHS012, IC695PSD040, IC695ETM001, IC646MPP101)	Active
IC695STK007	RX3i Power PACKage 7 Starter Kit includes (one each IC695CPU305, IC695CHS012, IC695PSD040, IC646MPP101)	Active
IC695STK010	RX3i CPE 305, RX3i PROFINET Controller Module, RX3i 7-slot base, RX3i AC Power Supply, RX3i 8 Point Input Simulator, RX3i 16 Point DC Outlet Module, VersaMax PROFINET Slave Module, VersaMax AC Power Supply, Mixed Discrete Module, Input Simulator, I/O Base, Proficy* Machine Edition Professional Software	Active

Demo Cases

IC695DEM001	RX3i Power PACKage 1 Demo Case that includes CPU, P/S, discrete I/O and analog I/O, high speed counter, Ethernet and analog simulator. Proficy Machine Edition Professional Edition included.	Active
IC695DEM002	RX3i Power PACKage 2 Demo Case that includes RX3i and QP Control/View. Includes CPU, P/S, discrete I/O and analog I/O, Active Ethernet, analog simulator, 6" TFT QuickPanel View/Control. Proficy Machine Edition Professional Edition included.	
IC695DEM004	Beta i Series 1-Axis Motion Demo Case. Demo case is a self contained table top demo that includes a DSM324i module, Beta i motor and amplifier prewired for connection to a DSM324i motion module. The cables (1 meter) for connection to the DSM324i 5 V I/O and FSSB fiber optic command interface are included. Demo includes an E-stop push button and toggle switches for 5 DSM324i I/O points.	Active

IC694 Rack to Rack Expansion Cables

IC693CBL300	Cable, I/O Base Expansion, 1 Meter, Shielded	Active
IC693CBL301	Cable, I/O Base Expansion, 2 Meters, Shielded	Active
IC693CBL302	Cable, I/O Base Expansion, 15 Meter, Shielded with built-in terminator	Active
IC693CBL312	Cable, I/O Base Expansion, 0.15 Meter, Shielded	Active
IC693CBL313	Cable, I/O Base Expansion, 8 Meters, Shielded	Active
IC693CBL314	Cable, I/O Base Expansion, 15 Meters, Shielded with no built-in terminator	Active
IC693ACC307	I/O Bus Terminator Plug	Active

Configuration Guidelines

When configuring a RX3i the following guidelines should be considered:

1. IC695 part numbers can only be installed in a Universal Rack (IC695CHSxxx).
2. CPU, NIU and AC Power Supply require 2 slots each on the base plate.
3. IC695 I/O modules and high density IC694 I/O modules require a terminal block assembly. IC694TBSxxx (spring clamp termination) or IC694TBBxxx (box style termination) are required.
4. If the CPU is powered down frequently a high capacity battery should be considered. (IC693ACC302)

Examples of Typical Application

Configuration for Controller (Example application requiring (120) 24 VDC inputs and (80) Relay outputs AC power supply)

Backplane Slots Required	Power Supply Current Required (mA)	Qty	Part Number	Description
2	1000 mA @ 3.3 VDC; 1000 mA @ 5 VDC	1	IC695CPE310	CPU with two built-in serial ports
2		1	IC695PSA040	120/240 VAC, 125 VDC Power Supply, current available 9 Amps @ 3.3 VDC; 6 Amps @ 5 VDC; 1.6 Amps @ 24 VDC maximum
	600 mA @ 3.3 VDC; 240 mA @ 5 VDC	1	IC695CHS016	16 Slot Universal Base
4	1200 @ 5 V	4	IC694MDL660	Discrete Input Module, 24 VDC Positive Logic, 32 points (Requires terminal block)
5	35 mA @ 5 V; 110 mA @ 24 VDC Relay	5	IC694MDL940	Discrete Output Module, Relay 2.0 A per point Form A, 16 points (Terminal block included).
		4	IC694TBB032	Terminal Block, Box Style
		1	IC646MPP001	Logic Developer -PLC Professional
13	Total current from power supply required: 2475 mA @ 5 V; 1600 @ 3.3 V; 110 mA @ 24 VDC Relay. Only one power supplied needed.			

Options to consider

	840 mA @ 3.3 VDC; 614 mA @ 5 VDC	1	IC695ETM001	Ethernet module 10/100Mbps
		1	IC690PWR024	24 VDC, 5 Amp Output Power and 120/230 VAC Input Power Power Supply
		1	IC754VSI06STD	QuickPanel View Intermediate 6 inch STN Touch Operator Interface